
ST-A 10/9000A-1-ST



Colours	Article no.	EAN
grey	659387	4043544785862
black	659388	4043544785879
white	659389	4043544785886



Description

- surface-mounted track with data bus (length: 1000 mm)
- also suitable for 3-phase track adapters without bus function
- realisation of lighting tasks with DALI technology
- 6-conductor track with three separately controllable current circuits
- extruded aluminium profile which also functions as earth
- length can be adjusted on site by easily shortening the track (cutting tool ST-ZCUT/S-9000/T-N required for shortening the copper conductors)

LOVE TO SHINE

(43)

CE

- · easy ceiling mounting with pre-punched oval mounting holes
- mechanical load diagramm see additional data sheet
- max. electrical load: AC mains power supply 3.6 kVA, 3-phase network 3 x 3.6 kVA = 10.8 kVA
- rated current and voltage: 16 A / 440 V (1 A / 50 V AC FELV)
- system components to be ordered separately

Dimensions / Weights

Length	1000 mm
Width	31 mm
Height	38 mm
Net weight	0.88 kg
Gross weight	0.93 kg







Accessories



EU 36 universal hook



EU 37 cap for universal hook



LA 30 SA-NORDIC 3-phase track adapter for wire-rope suspension



ST-A CAP/9004 end cover for surface-mounted track



ST-A F/PE-L/9002 end feed-in with polarity left



ST-A F/PE-R/9001 end feed-in with polarity right



ST-A FLEX/9018 flexible connector



ST-A I/9010 electric linear connector



ST-A L/PE-IN/9011 L-connector with polarity inside



ST-A L/PE-OUT/9012 L-connector with polarity outside



ST-A P/19/S-9000-P3 pendant-rod suspension (length: 1000 mm)



ST-A S/9000-KIT4/1500 wire-rope suspension (length: 1500 mm) + fixing clamp





Accessories



ST-A S/9000-KIT4/3000 wire-rope suspension (length: 3000 mm) + fixing clamp



ST-A S/9000-KIT4/5000 wire-rope suspension (length: 5000 mm) + fixing clamp



ST-A S/S-9000-111 ceiling bracket



ST-A S/S-9000-116 ceiling bracket with Reutlinger



ST-A S/S-9000-131 fixing clamp



ST-A S28 wire-rope suspension 2-fold with stabilizer



ST-A T/PE-IN-L/9015 T-connector with polarity inside left



ST-A T/PE-IN-R/9016 T-connector with polarity inside right



ST-A T/PE-OUT-L/9013 T-connector with polarity outside left



ST-A T/PE-OUT-R/9014 T-connector with polarity outside right



ST-A X/9017 ST-IE/9003 electric linear connector X-connector (inside) ST-IM/S-9000-322-LA mechanical coupler 1. (outside)



3-phase track adapter



ST-Z LA 30 M10 3-phase track adapter with thread nipple M10



ST-Z LA 30 M13 3-phase track adapter with thread nipple M13



ST-Z LAB 30 M13 3-phase track bus adapter with thread nipple M13





ST-A 10/9000A-1-ST

Accessories



ST-ZCUT/S-9000/T-N cutting tool



ST-ZSCHUKO/4230V socket adapter for 3-phase track