




## EL 303.5/B



Colours	Article no.	EAN
black	653093	4043544618207
silver	653094	4043544618214
white	653095	4043544618221



## Description

- tube-mounted spotlight in separated design for special large-area lighting of bakery products
- suitable for tube diameters from Ø 50 mm
- luminaire rotates through 355° and light-head pivots through 140°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with design-integrated passive cooling
- specially curved reflector with hammered optics made from ultra-pure aluminium for very high luminous efficiency
- light-head made from die-cast aluminium
- ballast housing made from aluminium
- clear safety glass
- clamping bracket for mounting via screw fixing
- 3-pole plug connection to mains
- ballast (LED converter) integrated

## Standard options



## Special options



## Lighting data / Norms


Lamps	LED Spot Bakery
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	40.0 W
Luminaire luminous flux	4470 lm
System efficiency	111.75 lm/W
Module efficiency	142.00 lm/W
UGR class	≤28
Beam angle	75°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

## Dimensions / Weights


Length	215 mm
Width	117 mm
Height	319 mm
Net weight	2.68 kg
Gross weight	2.82 kg

# EL 303.5/B

EuroLED 300 | Tube-Mounted (1xLED 40W BAKERY 4470lm 75°)



	C0	C90	C180	C270
0°	810	810	810	810
15°	581	771	581	771
30°	385	645	385	645
45°	29	421	29	421
60°	11	149	11	149
75°	0	5	0	5
90°	0	0	0	0
cd / 1000 lm				



<b>η</b>	LED
Efficiency	112 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	40 W
<b>UGR</b>	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.5
UGR C90/C270	28.4
CIE Flux Codes	77 98 100 100 100
Ra/CRI	---

LTS

## Accessories



**ZBK 97**  
anti-glare flaps