

FLCK-W 415.200.40




Description

- powerful high-bay luminaire with lens optics for highest luminous efficiency
- no inner pollution by integrated dust filter
- light-head pivots through 36°
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management with design-integrated passive cooling
- light-head made from die-cast aluminium
- mounting and fixing bracket for ballast made from sheet steel
- lens optics made from clear polycarbonate
- screw mounting via wall bracket
- 3-pole plug connection to mains
- ballast (LED converter) integrated

Special options



Colours	Article no.	EAN
silver	652486	4043544612045




Lighting data / Norms

Lamps	LED Modul / CRI 80 / 4000 K
Lifetime	L85 B20 50.000 h
System power	152.0 W
Luminaire luminous flux	19980 lm
System efficiency	131.44 lm/W
UGR class	≤25
Beam angle	66°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Impact resistance	IK10
Type of protection	IP66

Dimensions / Weights


Outer diameter	415 mm
Height	177 mm
Net weight	7.40 kg
Gross weight	7.79 kg



FLCK-W 415.200.40

FLCK-W 415.200.40

FLC | Wall (1xLED 152W 840/4000K 19980lm 66°)



	C0	C90	C180	C270
0°	933	933	933	933
15°	867	867	867	867
30°	611	611	611	611
45°	47	47	47	47
60°	19	19	19	19
75°	11	11	11	11
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
C0-C180 Plane		
3.0	3.94	2071.9
6.0	7.88	518.0
9.0	11.81	230.2
12.0	15.75	129.5
15.0	19.69	82.9

η	LED
Efficiency	131 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	152 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	23.0
UGR C90/C270	23.0
CIE Flux Codes	92 97 99 100 100
Ra/CRI	>80

LTS