


BIXXL 206.40.25.2/DALI-EU



Colours	Article no.	EAN
black	646527	4043544537522
silver	646528	4043544537539
white	646529	4043544537546








Description

- flexible track-mounted spotlight in separated design with organically formed light-head
- luminaire rotates through 355° and light-head pivots through 90°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with design-integrated passive cooling
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- light-head made from die-cast aluminium
- ballast housing made from aluminium
- clear and reflection-free EnergyVision safety glass
- 3-phase track adapter DALI (Eutrac)
- ballast (LED converter DALI, dimmable) integrated

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot / CRI 80 / 4000 K
EPREL light sources	848105
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	59.0 W
Luminaire luminous flux	6050 lm
System efficiency	102.54 lm/W
Module efficiency	167.61 lm/W
UGR class	≤19
Beam angle	25°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Length	136 mm
Width	170 mm
Height	195 mm
Diameter of light head	123 mm
Net weight	1.60 kg
Gross weight	1.80 kg

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024


BIXXL 206.40.25.2/DALI-EU

BixxL 200 (1xLED 59W 840/4000K 6050lm 25 °)



	C0	C90	C180	C270
0°	3510	3510	3510	3510
15°	1366	1366	1366	1366
30°	375	375	375	375
45°	6	6	6	6
60°	3	3	3	3
75°	2	2	2	2
90°	0	0	0	0

cd / 1000 lm



η	LED
Efficiency	103 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	59 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.1
UGR C90/C270	19.1
CIE Flux Codes	99 99 100 100 100
Ra/CRI	>80

LTS

Accessories



ZBK 98
anti-glare flaps



ZBW 84
honeycomb louvre

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024