




FLIR 100.1030.35/DALI



Colours	Article no.	EAN
black	641723	4043544472694
silver	641724	4043544472700
white	641725	4043544472717



Description

- recessed spotlight with optical design variants and wide range of applications
- light-head pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling (heat sink made from die-cast aluminium)
- high performance specular aluminium reflector with precise symmetrical beam characteristic for highest luminous efficiency and best glare-free lighting
- front/recessed ring made from die-cast zinc with clear light effect ring (other decor/light effect rings and deco glasses are available as options)
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter DALI, dimmable) included (external placement)

Notes

The cut-out = 68 mm is only valid for plasterboard ceilings. For other types of ceilings the cut-out = 70 mm.

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	988880
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	15.0 W
Luminaire luminous flux	max. 1360 lm
System efficiency	84.66 lm/W
Module efficiency	134.38 lm/W
UGR class	≤28
Beam range	Flood
Beam angle	42°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	II
Type of protection	IP20

Dimensions / Weights

Outer diameter	80 mm
Height	92 mm
Cut-out (Ø)	68 mm
Ceiling thickness	1.0 - 25.0 mm
Recessed depth	90 mm
Net weight	0.48 kg
Gross weight	0.50 kg

Recessed Downlights · Flixx 100 Round


FLIR 100.1030.35/DALI



FLIR 100.1030.35/DALI

FLIR 100.1030.35/DALI

Flixx 100 Round (FLIRZ 100.24, 1xLED 15W 830/3000K 1270lm 35°)



	C0	C90	C180	C270
0°	1350	1350	1350	1350
15°	977	977	977	977
30°	389	389	389	389
45°	109	109	109	109
60°	41	41	41	41
75°	17	17	17	17
90°	0	0	0	0


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	2.44	190.5
6.0	4.88	47.6
9.0	7.33	21.2
12.0	9.77	11.9
15.0	12.21	7.6

η	LED
Efficiency	85 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	26.9
UGR C90/C270	26.9
CIE Flux Codes	82 94 99 100 100
Ra/CRI	>80

LTS

FLIR 100.1030.35/DALI

Flixx 100 Round (FLIRZ 100.05, 1xLED 15W 830/3000K 1360lm 35°)



	C0	C90	C180	C270
0°	1666	1666	1666	1666
15°	1246	1246	1246	1246
30°	426	426	426	426
45°	36	36	36	36
60°	23	23	23	23
75°	12	12	12	12
90°	1	1	1	1


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	2.31	251.7
6.0	4.63	62.9
9.0	6.94	28.0
12.0	9.26	15.7
15.0	11.57	10.1

η	LED
Efficiency	91 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	24.4
UGR C90/C270	24.4
CIE Flux Codes	91 96 99 100 100
Ra/CRI	>80

LTS

FLIR 100.1030.35/DALI

Flixx 100 Round (FLIRZ 100.25, 1xLED 15W 830/3000K 1310lm 35°)



	C0	C90	C180	C270
0°	1622	1622	1622	1622
15°	1213	1213	1213	1213
30°	432	432	432	432
45°	46	46	46	46
60°	26	26	26	26
75°	9	9	9	9
90°	0	0	0	0

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	2.33	236.1
6.0	4.66	59.0
9.0	6.99	26.2
12.0	9.32	14.8
15.0	11.65	9.4

η	LED
Efficiency	87 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	15 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	23.5
UGR C90/C270	23.5
CIE Flux Codes	91 97 99 100 100
Ra/CRI	>80

LTS

FLIR 100.1030.35/DALI

Accessories



FLIRZ 100.01
decorative ring black



FLIRZ 100.02
decorative ring silver



FLIRZ 100.03
decorative ring white



FLIRZ 100.04
light effect ring opal



FLIRZ 100.05
light effect ring clear



FLIRZ 100.06
light effect ring red matt



FLIRZ 100.07
light effect ring yellow matt



FLIRZ 100.08
light effect ring blue matt



FLIRZ 100.16
light effect ring red translucent




FLIRZ 100.17
light effect ring yellow translucent



FLIRZ 100.18
light effect ring blue translucent



FLIRZ 100.19
light effect ring orange translucent



FLIRZ 100.24
decorative glass opal



FLIRZ 100.25
decorative glass clear



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting