


GLOB 300.2030.2/DALI



Colours	Article no.	EAN
white	649427	4043544570826







Description

- pendant luminaire with a simplistic and classic design
- outstanding ease of maintenance
- no UV and thermal emissions
- light component: direct 55% / indirect 45%
- ceiling canopy and decor plate for cable storage in white
- half-sphere ceiling canopy made from white ABS
- white textile cable with filigree wire-rope suspension (length: 2000 mm)
- adjustable cable length on ceiling canopy
- light-ball made from opal acrylic glass
- easy mounting of the ceiling canopy
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated in the luminaire

Standard options

4000 K

Lighting data / Norms

Lamps	LED Modul / CRI 80 / 3000 K
Lifetime	L80 B50 100.000 h
System power	20.0 W
Luminaire luminous flux	2560 lm
System efficiency	128.00 lm/W
UGR class	≤19
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights


Outer diameter	300 mm
Height	300 mm
Net weight	2.50 kg
Gross weight	2.61 kg

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024

GLOB 300.2030.2/DALI

GLOB 300.2030.2/DALI

Globia (1xLED 20W 830/3000K 2560lm)



	C0	C90	C180	C270
0°	80	80	80	80
30°	81	81	81	81
60°	85	85	85	85
90°	86	86	86	86
120°	76	76	76	76
150°	63	63	63	63
180°	41	41	41	41

cd / 1000 lm

LDC unsuitable for cone representation.
The C0 angle is oversized.

η	LED
Efficiency	128 lm/W
Direct/Indirect	↓ 53% / ↑ 47%
System Power	20 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	18.4
UGR C90/C270	18.4
CIE Flux Codes	24 49 74 53 100
Ra/CRI	>80

LTS

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024