




IMOL 41.1130.1 SENSO




Colours	Article no.	EAN
astro silver	633993	4043544359896
carbongrey	633994	4043544359902
white	633995	4043544359919



Description

- free-standing luminaire with direct-indirect illumination for uniform and glare-free workplace lighting
- light component: direct 40% / indirect 60%
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from polyamide
- round stand made from silver anodised aluminium (applies for all luminaire colours)
- base made from die-cast with fine structure
- automatic sensors for presence and daylight
- diffusers for direct light component made from prismatic acrylic glass, diffusers for indirect light component made from clear acrylic glass
- central plug connection to mains (length of connecting cable: approx. 3000 mm), black cable
- ballast (LED converter) integrated

Standard options



Lighting data / Norms


Lamps	LED linear / CRI 80 / 3000 K
EPREL light sources	833894 833877
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	109.0 W
Luminaire luminous flux	8400 lm
System efficiency	77.06 lm/W
Module efficiency	177.91 lm/W
UGR class	≤16
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights

Length	661 mm
Width	430 mm
Height	1935 mm
Net weight	11.93 kg
Gross weight	12.56 kg

IMOL 41.1130.1 SENSO

Imola LED (1xLED 109W 830/3000K 8400lm)



	C0	C90	C180	C270
0°	237	237	237	237
30°	183	185	183	185
60°	21	20	21	20
90°	0	1	0	1
120°	93	91	93	91
150°	188	184	188	184
180°	209	209	209	209
cd / 1000 lm				

LDC unsuitable for cone representation.
The C0 angle is oversized.

η	LED
Efficiency	77 lm/W
Direct/Indirect	↓ 41% / ↑ 59%
System Power	109 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	11.4
UGR C90/C270	11.9
CIE Flux Codes	71 94 98 41 100
Ra/CRI	>80

LTS

Accessories



ZBC 001
remote control