



JETT 102.927.35.2



Colours	Article no.	EAN
silver	664940	4043544740762
black	664941	4043544740779
white	664942	4043544740786



Description

- flexible track-mounted spotlight in separated design with cylindrical light-head
- luminaire rotates through 355° and light-head pivots through 180°
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from die-cast aluminium
- innovative thermal management with design-integrated passive cooling
- high performance specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- ballast housing made from aluminium
- clear safety glass
- 3-phase track adapter
- ballast (LED converter) integrated

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot / CRI 90 / 2700 K
EPREL light sources	847889
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	20.8 W
Luminaire luminous flux	2050 lm
System efficiency	98.55 lm/W
Module efficiency	133.10 lm/W
UGR class	≤22
Beam angle	35°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Length	115 mm
Width	148 mm
Height	175 mm
Diameter of light head	103 mm
Net weight	1.27 kg
Gross weight	1.34 kg

JETT 102.927.35.2

Jett 100 (1xLED 21W 927/2700K 2050lm 35°)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	2069	2069	2069	2069
15°	1354	1354	1354	1354
30°	392	392	392	392
45°	23	23	23	23
60°	13	13	13	13
75°	7	7	7	7
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	2.03	471.3
6.0	4.06	117.8
9.0	6.08	52.4
12.0	8.11	29.5
15.0	10.14	18.9

η	LED
Efficiency	98 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	21 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.7
UGR C90/C270	19.7
CIE Flux Codes	95 98 99 100 100
Ra/CRI	>90

LTS

Accessories



FOCUS 100.1

superior optic with focusable biconvex lens for accent lighting



ST-A 10/9000A-1-ST

surface-mounted track ONETrack Advance with data bus (length: 1000 mm)



ST-A 20/9000A-2-ST

surface-mounted track ONETrack Advance with data bus (length: 2000 mm)



ST-A 30/9000A-3-ST

surface-mounted track ONETrack Advance with data bus (length: 3000 mm)



ST-A 40/9000A-4-ST

surface-mounted track ONETrack Advance with data bus (length: 4000 mm)



ST-A MONO/9000-BPU-D

3-phase surface-mounted monopoint with bus option



ST-E 10/9000-1-R

recessed track ONETrack with data bus (length: 1000 mm)



ST-E 20/9000-2-R

recessed track ONETrack with data bus (length: 2000 mm)



ST-E 30/9000-3-R

recessed track ONETrack with data bus (length: 3000 mm)



ST-E 40/9000-4-R

recessed track ONETrack with data bus (length: 4000 mm)



ST-E MONO/9000-BPU-D

3-phase recessed monopoint with bus option



ZBK 96

anti-glare flaps

Track-Mounted Spotlights · Jett 100



JETT 102.927.35.2

Accessories



ZBW 83
honeycomb louvre