


JETT 102.930.15.2/DALI-ST



Colours	Article no.	EAN
silver	667679	4043544770172
black	667680	4043544770189
white	667681	4043544770196



Description

- flexible track-mounted spotlight in separated design with cylindrical light-head
- luminaire rotates through 355° and light-head pivots through 180°
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from die-cast aluminium
- innovative thermal management with design-integrated passive cooling
- high performance specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- ballast housing made from aluminium
- clear safety glass
- 3-phase track adapter DALI (ONETrack)
- ballast (LED converter DALI, dimmable) integrated

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot / CRI 90 / 3000 K
EPREL light sources	851023
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	20.8 W
Luminaire luminous flux	2280 lm
System efficiency	109.61 lm/W
Module efficiency	132.78 lm/W
UGR class	≤19
Beam angle	15°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Length	115 mm
Width	148 mm
Height	182 mm
Diameter of light head	103 mm
Net weight	1.30 kg
Gross weight	1.37 kg

JETT 102.930.15.2/DALI-ST

Jett 100 (1xLED 21W 930/3000K 2280lm 15°)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	6286	6286	6286	6286
15°	970	970	970	970
30°	408	408	408	408
45°	9	9	9	9
60°	7	7	7	7
75°	0	0	0	0
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	0.84	1592.6
6.0	1.67	398.1
9.0	2.51	177.0
12.0	3.34	99.5
15.0	4.18	63.7

η	LED
Efficiency	109 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	21 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	17.3
UGR C90/C270	17.3
CIE Flux Codes	98 100 100 100 100
Ra/CRI	>90

LTS

Accessories



FOCUS 100.1

superior optic with focusable biconvex lens for accent lighting



ST-A 10/9000A-1-ST

surface-mounted track ONETrack Advance with data bus (length: 1000 mm)



ST-A 20/9000A-2-ST

surface-mounted track ONETrack Advance with data bus (length: 2000 mm)



ST-A 30/9000A-3-ST

surface-mounted track ONETrack Advance with data bus (length: 3000 mm)



ST-A 40/9000A-4-ST

surface-mounted track ONETrack Advance with data bus (length: 4000 mm)



ST-A MONO/9000-BPU-D

3-phase surface-mounted monopoint with bus option



ST-E 10/9000-1-R

recessed track ONETrack with data bus (length: 1000 mm)



ST-E 20/9000-2-R

recessed track ONETrack with data bus (length: 2000 mm)



ST-E 30/9000-3-R

recessed track ONETrack with data bus (length: 3000 mm)



ST-E 40/9000-4-R

recessed track ONETrack with data bus (length: 4000 mm)



ST-E MONO/9000-BPU-D

3-phase recessed monopoint with bus option



ZB-OR DONGLE

Organic Response IR dongle kit

JETT 102.930.15.2/DALI-ST

Accessories



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-T SENSOR
Organic Response sensor for track mounting



ZBK 96
anti-glare flaps



ZBW 83
honeycomb louvre