

Recessed Spotlights · Jett 150


# JETT 152.927.35



| Colours | Article no. | EAN |
|---|---|---|
| silver | 665277 | 4043544744487 |
| black | 665278 | 4043544744494 |
| white | 665279 | 4043544744500 |




## Description

- flexible recessed spotlight with cylindrical light-head
- light-head completely extracts, rotates through 355° and pivots through 90°
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from die-cast aluminium
- innovative thermal management with design-integrated passive cooling
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- recessed frame made from aluminium and sheet steel
- concealing plate for ceiling opening
- clear safety glass
- tool-free ceiling mounting via automatic quick clamping (automatic adjustment of the ceiling thickness)
- connection to ballast via luminaire cable with integrated plug
- ballast (LED converter) included (external placement)

## Standard options

3000 K · 4000 K · BAKERY · MEAT · DALI · 15° · 25° · 50°

## Special options

3500 K · CRI 80 SDCM3 · MEAT · PRODUCE · FASHION · TWL · CASAMBI

## Lighting data / Norms

| | |
|---|---|
| Lamps | LED Spot / CRI 90 / 2700 K |
| Lifetime | L90 B50 50.000 h<br>L80 B50 100.000 h<br>L80 B20 50.000 h |
| System power | 21.0 W |
| Luminaire luminous flux | 2050 lm |
| System efficiency | 98.55 lm/W |
| Module efficiency | 133.10 lm/W |
| UGR class | ≤22 |
| Beam angle | 35° |
| Supply voltage | 220 - 240 V / 50 - 60 Hz |
| Protection class | III |
| Type of protection | IP20 |


## Dimensions / Weights

| | |
|---|---|
| Outer diameter | 170 mm |
| Height | 198 mm |
| Cut-out (Ø) | 157 mm |
| Ceiling thickness | 5.0 - 50.0 mm |
| Recessed depth | 195 mm |
| Diameter of light head | 103 mm |
| Net weight | 1.87 kg |
| Gross weight | 1.97 kg |

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024


# JETT 152.927.35

Jett 150 (1xLED 21W 927/2700K 2050lm 35°)




| | C0 | C90 | C180 | C270 |
|---|---|---|---|---|
| 0° | 2069 | 2069 | 2069 | 2069 |
| 15° | 1354 | 1354 | 1354 | 1354 |
| 30° | 392 | 392 | 392 | 392 |
| 45° | 23 | 23 | 23 | 23 |
| 60° | 13 | 13 | 13 | 13 |
| 75° | 7 | 7 | 7 | 7 |
| 90° | 0 | 0 | 0 | 0 |

cd / 1000 lm




| | |
|---|---|
| η | LED |
| Efficiency | 98 lm/W |
| Direct/Indirect | ↓ 100% / ↑ 0% |
| System Power | 21 W |
| **UGR** | X=4H, Y=8H |
| Reflection factors | 70/50/20 |
| UGR C0/C180 | 19.7 |
| UGR C90/C270 | 19.7 |
| CIE Flux Codes | 95 98 99 100 100 |
| Ra/CRI | >90 |

LTS

## Accessories



**FOCUS 100.1**
superior optic with focusable biconvex lens for accent lighting




**ZBK 96**
anti-glare flaps



**ZBW 83**
honeycomb louvre



**ZDAR 158.200-265**
compensation ring for ceiling cut-outs from 200 to 265 mm



**ZDVR 0157**
ceiling reinforcement ring

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024