


JETT 152.930.50/DALI



Colours	Article no.	EAN
silver	665304	4043544744753
black	665305	4043544744760
white	665306	4043544744777







Description

- flexible recessed spotlight with cylindrical light-head
- light-head completely extracts, rotates through 355° and pivots through 90°
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from die-cast aluminium
- innovative thermal management with design-integrated passive cooling
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- recessed frame made from aluminium and sheet steel
- concealing plate for ceiling opening
- clear safety glass
- tool-free ceiling mounting via automatic quick clamping (automatic adjustment of the ceiling thickness)
- connection to ballast via luminaire cable with integrated plug
- ballast (LED converter DALI, dimmable) included (external placement)

Standard options

2700 K · 4000 K · BAKERY · MEAT · 15° · 25° · 35°

Special options

3500 K · CRI 80 SDCM3 · MEAT · PRODUCE · FASHION · TWL · MinusBlue · CASAMBI

Lighting data / Norms

Lamps	LED Spot / CRI 90 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	21.0 W
Luminaire luminous flux	2090 lm
System efficiency	100.48 lm/W
Module efficiency	141.19 lm/W
UGR class	≤22
Beam angle	50°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	III
Type of protection	IP20


Dimensions / Weights

Outer diameter	170 mm
Height	198 mm
Cut-out (Ø)	157 mm
Ceiling thickness	5.0 - 50.0 mm
Recessed depth	195 mm
Diameter of light head	103 mm
Net weight	1.88 kg
Gross weight	1.98 kg

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024


JETT 152.930.50/DALI

Jett 150 (1xLED 21W 930/3000K 2090lm 50°)



	C0	C90	C180	C270
0°	1395	1395	1395	1395
15°	1187	1187	1187	1187
30°	490	490	490	490
45°	25	25	25	25
60°	14	14	14	14
75°	8	8	8	8
90°	0	0	0	0

cd / 1000 lm



η	LED
Efficiency	100 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	21 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	21.1
UGR C90/C270	21.1
CIE Flux Codes	94 98 99 100 100
Ra/CRI	>90

LTS

Accessories



FOCUS 100.1
superior optic with focusable biconvex lens for accent lighting



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting




ZBK 96
anti-glare flaps



ZBW 83
honeycomb louvre



ZDAR 158.200-265
compensation ring for ceiling cut-outs from 200 to 265 mm



ZDVR 0157
ceiling reinforcement ring

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024