


BTN-P 302.40.15.3



Colours	Article no.	EAN
black	651238	4043544602725
silver	651239	4043544602732
white	651240	4043544602749



Description

- pendant luminaire for general and accent lighting
- light-insert rotates through 350° and pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management with passive cooling (internal heat sink made from aluminium)
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- cylindrical aluminium housing with light-insert made from die-cast zinc
- ceiling box with feed-in made from ABS (D = 82 mm, H = 35 mm)
- height-adjustable wire-ropo suspension (length: 1500 mm)
- transparent connecting cable
- clear safety glass
- ceiling box for screw mounting (in luminaire colour)
- 5-pole terminal block
- ballast (LED converter) integrated in the luminaire

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot / CRI 80 / 4000 K
EPREL light sources	848119
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	27.0 W
Luminaire luminous flux	2850 lm
System efficiency	105.55 lm/W
Module efficiency	160.37 lm/W
UGR class	≤19
Beam range	Spot
Beam angle	14°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights


Outer diameter	140 mm
Height	167 mm
Net weight	2.28 kg
Gross weight	2.65 kg

BTN-P 302.40.15.3

BTN-P 302.40.15.3

Button 300 | Pendant (1xLED 27W 840/4000K 2850lm 15°)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	7054	7054	7054	7054
15°	937	937	937	937
30°	372	372	372	372
45°	12	12	12	12
60°	12	12	12	12
75°	3	3	3	3
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

C0-C180 Plane		
3.0	0.75	2233.8
6.0	1.50	558.4
9.0	2.24	248.2
12.0	2.99	139.6
15.0	3.74	89.4

η	LED
Efficiency	106 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	27 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.2
UGR C90/C270	19.2
CIE Flux Codes	97 99 100 100 100
Ra/CRI	>80

LTS