


LK-LED 070.1040.1125.1/DALI



Description

- light-insert with integrated LED strips
- reflector made from white-painted aluminium
- no UV and thermal emissions
- almost all strip light lengths can be realised
- 5-pole through-wiring kit included
- curved PMMA diffuser for uniform light distribution
- tool-free snapping into Lichtkanal profile
- 5-pole terminal block, pre-fabricated for through-wiring
- ballast (LED converter DALI, dimmable) integrated

Notes


The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at dT = 10 Kelvin.

Standard options



Colours	Article no.	EAN
	664869	4043544740052

Special options





Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	18.3 W
Luminaire luminous flux	max. 2020 lm
System efficiency	102.18 lm/W
Module efficiency	164.17 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I


Dimensions / Weights

Length	1125 mm
Width	57 mm
Height	52 mm
Net weight	1.57 kg
Gross weight	1.65 kg



LK-LED 070.1040.1125.1/DALI

Lichtkanal 070 - Light-Insert (AOB, 1xLED 18W 840/4000K 1870lm)



	C0	C90	C180	C270
0°	408	408	408	408
15°	382	382	382	382
30°	314	314	314	314
45°	229	226	229	226
60°	142	138	142	138
75°	61	56	61	56
90°	1	0	1	0


cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	6.97 6.84	84.7
6.0	13.95 13.68	21.2
9.0	20.92 20.53	9.4
12.0	27.89 27.37	5.3
15.0	34.87 34.21	3.4

η	LED
Efficiency	104 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	18 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	23.4
UGR C90/C270	23.0
CIE Flux Codes	51 81 96 100 100
Ra/CRI	>80

LTS

Lichtkanal 070 - Light-Insert (APB, 1xLED 18W 840/4000K 1730lm)



	C0	C90	C180	C270
0°	570	570	570	570
15°	521	535	521	535
30°	356	428	356	428
45°	195	260	195	260
60°	76	89	76	89
75°	26	28	26	28
90°	0	0	0	0


cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	4.40 5.57	109.6
6.0	8.80 11.14	27.4
9.0	13.20 16.72	12.2
12.0	17.60 22.29	6.8
15.0	22.00 27.86	4.4

η	LED
Efficiency	96 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	18 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	18.9
UGR C90/C270	19.9
CIE Flux Codes	65 90 98 100 100
Ra/CRI	>80

LTS

Lichtkanal 070 - Light-Insert (AOV-001/003/005.1, 1xLED 18W 840/4000K 2020lm)



	C0	C90	C180	C270
0°	325	325	325	325
30°	262	247	262	247
60°	145	105	145	105
90°	43	1	43	1
120°	30	1	30	1
150°	14	1	14	1
180°	0	0	0	0


cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	8.76 6.55	73.0
6.0	17.52 13.10	18.2
9.0	26.28 19.65	8.1
12.0	35.03 26.21	4.6
15.0	43.79 32.76	2.9

η	LED
Efficiency	112 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	18 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	25.2
UGR C90/C270	21.9
CIE Flux Codes	46 75 92 89 100
Ra/CRI	>80

LTS

Lichtkanal 070 - Light-Insert (AOV-002/005.2, 1xLED 18W 840/4000K 2020lm)



	C0	C90	C180	C270
0°	325	325	325	325
30°	262	247	262	247
60°	145	105	145	105
90°	43	1	43	1
120°	30	1	30	1
150°	14	1	14	1
180°	0	0	0	0

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	8.76 6.55	73.0
6.0	17.52 13.10	18.2
9.0	26.28 19.65	8.1
12.0	35.03 26.21	4.6
15.0	43.79 32.76	2.9

η	LED
Efficiency	112 lm/W
Direct/Indirect	↓ 89% / ↑ 11%
System Power	18 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	25.2
UGR C90/C270	21.9
CIE Flux Codes	46 75 92 89 100
Ra/CRI	>80

LTS