


LK-LED 070.1140.1685.1




Description

- light-insert with integrated LED strips
- reflector made from white-painted aluminium
- no UV and thermal emissions
- almost all strip light lengths can be realised
- 5-pole through-wiring kit included
- curved PMMA diffuser for uniform light distribution
- tool-free snapping into Lichtkanal profile
- 5-pole terminal block, pre-fabricated for through-wiring
- ballast (LED converter) integrated


Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $\Delta T = 10$ Kelvin.

Standard options



Colours	Article no.	EAN
	664920	4043544740564



Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	66.0 W
Luminaire luminous flux	max. 7220 lm
System efficiency	109.39 lm/W
Module efficiency	164.17 lm/W
UGR class	≤28
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I


Dimensions / Weights

Length	1685 mm
Width	57 mm
Height	52 mm
Net weight	2.12 kg
Gross weight	2.24 kg



LK-LED 070.1140.1685.1

Lichtkanal 070 - Light-Insert (AOV-001/003/005.1, 1xLED 66W 840/4000K 7220lm)



	C0	C90	C180	C270
0°	326	326	326	326
30°	263	249	263	249
60°	145	106	145	106
90°	42	2	42	2
120°	30	1	30	1
150°	14	1	14	1
180°	0	0	0	0


cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	8.66 6.63	261.9
6.0	17.31 13.27	65.5
9.0	25.97 19.90	29.1
12.0	34.62 26.53	16.4
15.0	43.28 33.16	10.5

η	LED
Efficiency	109 lm/W
Direct/Indirect	↓ 90% / ↑ 10%
System Power	66 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	28.2
UGR C90/C270	25.0
CIE Flux Codes	46 75 92 90 100
Ra/CRI	>80

LTS

Lichtkanal 070 - Light-Insert (AOV-002/005.2, 1xLED 66W 840/4000K 7220lm)



	C0	C90	C180	C270
0°	326	326	326	326
30°	263	249	263	249
60°	145	106	145	106
90°	42	2	42	2
120°	30	1	30	1
150°	14	1	14	1
180°	0	0	0	0


cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	8.66 6.63	261.9
6.0	17.31 13.27	65.5
9.0	25.97 19.90	29.1
12.0	34.62 26.53	16.4
15.0	43.28 33.16	10.5

η	LED
Efficiency	109 lm/W
Direct/Indirect	↓ 90% / ↑ 10%
System Power	66 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	28.2
UGR C90/C270	25.0
CIE Flux Codes	46 75 92 90 100
Ra/CRI	>80

LTS

Lichtkanal 070 - Light-Insert (AOB, 1xLED 66W 840/4000K 6600lm)



	C0	C90	C180	C270
0°	409	409	409	409
15°	383	384	383	384
30°	314	315	314	315
45°	227	227	227	227
60°	142	138	142	138
75°	62	56	62	56
90°	1	0	1	0


cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	6.92 6.83	300.0
6.0	13.84 13.67	75.0
9.0	20.76 20.50	33.3
12.0	27.68 27.34	18.8
15.0	34.60 34.17	12.0

η	LED
Efficiency	100 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	66 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	26.4
UGR C90/C270	26.0
CIE Flux Codes	51 81 96 100 100
Ra/CRI	>80

LTS

Lichtkanal 070 - Light-Insert (APB, 1xLED 66W 840/4000K 6290lm)



	C0	C90	C180	C270
0°	574	574	574	574
15°	526	538	526	538
30°	358	427	358	427
45°	197	257	197	257
60°	76	88	76	88
75°	26	27	26	27
90°	0	0	0	0

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	4.41 5.50	401.2
6.0	8.83 11.00	100.3
9.0	13.24 16.50	44.6
12.0	17.66 22.01	25.1
15.0	22.07 27.51	16.0

η	LED
Efficiency	95 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	66 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.1
UGR C90/C270	22.8
CIE Flux Codes	65 90 98 100 100
Ra/CRI	>80

LTS