



CDL 30.2040.02



Colours	Article no.	EAN
silver	660090	4043544689092
white	660091	4043544689108



Description

- recessed downlight for general lighting
- luminaire can be expanded with different optic decor rings and glasses
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling (heat sink made from die-cast aluminium)
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- front/recessed ring made from polycarbonate
- tool-free ceiling mounting via quick-action clamps (automatic adjustment of the ceiling thickness)
- connection to ballast via pre-fitted luminaire cable
- ballast (LED converter) included (external placement)

Notes

concrete casting surround available on demand.

Standard options



Special options



Lighting data / Norms


Lamps	LED Modul / CRI 80 / 4000 K
EPREL light sources	891017
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	22.0 W
Luminaire luminous flux	max. 2300 lm
System efficiency	104.54 lm/W
Module efficiency	122.35 lm/W
UGR class	≤25
Beam angle	75°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	III
Type of protection	IP20

Dimensions / Weights

Outer diameter	224 mm
Height	113 mm
Cut-out (Ø)	195 mm
Ceiling thickness	10.0 - 35.0 mm
Recessed depth	110 mm
Net weight	0.95 kg
Gross weight	1.00 kg

CDL 30.2040.02

Multi 30 (CDL ohne Dekor, 1xLED 22W 840/4000K 2300lm 75 °)




	C0	C90	C180	C270
0°	988	988	988	988
15°	870	870	870	870
30°	519	519	519	519
45°	148	148	148	148
60°	0	0	0	0
75°	0	0	0	0
90°	0	0	0	0

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	3.60	252.4
6.0	7.19	63.1
9.0	10.79	28.0
12.0	14.38	15.8
15.0	17.98	10.1

η	LED
Efficiency	105 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.1
UGR C90/C270	19.1
CIE Flux Codes	89 100 100 100 100
Ra/CRI	>80

LTS

Multi 30 (CDZ 3.01, 1xLED 22W 840/4000K 1960lm 75 °)




	C0	C90	C180	C270
0°	589	589	589	589
15°	557	557	557	557
30°	475	475	475	475
45°	228	228	228	228
60°	40	40	40	40
75°	17	17	17	17
90°	0	0	0	0

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	5.37	128.2
6.0	10.73	32.1
9.0	16.10	14.2
12.0	21.47	8.0
15.0	26.83	5.1

η	LED
Efficiency	89 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.6
UGR C90/C270	22.6
CIE Flux Codes	74 94 99 100 100
Ra/CRI	>80

LTS

Multi 30 (CDZ 3.08, 1xLED 22W 840/4000K 2200lm 75 °)




	C0	C90	C180	C270
0°	1060	1060	1060	1060
15°	928	928	928	928
30°	480	480	480	480
45°	84	84	84	84
60°	32	32	32	32
75°	12	12	12	12
90°	1	1	1	1

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	3.26	259.0
6.0	6.52	64.8
9.0	9.78	28.8
12.0	13.04	16.2
15.0	16.30	10.4

η	LED
Efficiency	100 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.9
UGR C90/C270	19.9
CIE Flux Codes	86 96 99 100 100
Ra/CRI	>80

LTS

Multi 30 (CDZ 3.35, 1xLED 22W 840/4000K 2220lm 75 °)



	C0	C90	C180	C270
0°	1081	1081	1081	1081
15°	867	867	867	867
30°	465	465	465	465
45°	114	114	114	114
60°	34	34	34	34
75°	15	15	15	15
90°	0	0	0	0

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	3.11	266.6
6.0	6.22	66.7
9.0	9.33	29.6
12.0	12.44	16.7
15.0	15.55	10.7


η	LED
Efficiency	101 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.9
UGR C90/C270	20.9
CIE Flux Codes	84 95 99 100 100
Ra/CRI	>80

LTS

CDL 30.2040.02

Multi 30 (CDZ 3.38, 1xLED 22W 840/4000K 2050lm 75 °)

— C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	697	697	697	697
15°	605	605	605	605
30°	393	393	393	393
45°	196	196	196	196
60°	84	84	84	84
75°	28	28	28	28
90°	0	0	0	0

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	3.89	158.8
6.0	7.78	39.7
9.0	11.68	17.6
12.0	15.57	9.9
15.0	19.46	6.4


— C0-C180 Plane

η	LED
Efficiency	93 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	24.6
UGR C90/C270	24.6
CIE Flux Codes	67 90 98 100 100
Ra/CRI	>80

LTS

Multi 30 (CDZ 3.39, 1xLED 22W 840/4000K 2210lm 75 °)

— C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	952	952	952	952
15°	839	839	839	839
30°	507	507	507	507
45°	154	154	154	154
60°	7	7	7	7
75°	5	5	5	5
90°	0	0	0	0

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	3.64	233.8
6.0	7.27	58.4
9.0	10.91	26.0
12.0	14.55	14.6
15.0	18.19	9.4


— C0-C180 Plane

η	LED
Efficiency	101 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.3
UGR C90/C270	19.3
CIE Flux Codes	87 99 100 100 100
Ra/CRI	>80

LTS

Multi 30 (CDZ 3.60, 1xLED 22W 840/4000K 2180lm 75 °)

— C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	676	676	676	676
15°	612	612	612	612
30°	477	477	477	477
45°	213	213	213	213
60°	38	38	38	38
75°	16	16	16	16
90°	0	0	0	0

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	4.81	163.9
6.0	9.61	41.0
9.0	14.42	18.2
12.0	19.22	10.2
15.0	24.03	6.6


— C0-C180 Plane

η	LED
Efficiency	99 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.3
UGR C90/C270	22.3
CIE Flux Codes	76 95 99 100 100
Ra/CRI	>80

LTS

Multi 30 (CDZ 3.61, 1xLED 22W 840/4000K 2190lm 75 °)

— C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	864	864	864	864
15°	728	728	728	728
30°	424	424	424	424
45°	169	169	169	169
60°	56	56	56	56
75°	19	19	19	19
90°	1	1	1	1

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	3.41	210.1
6.0	6.82	52.5
9.0	10.23	23.3
12.0	13.65	13.1
15.0	17.06	8.4

— C0-C180 Plane


η	LED
Efficiency	100 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.9
UGR C90/C270	22.9
CIE Flux Codes	75 93 99 100 100
Ra/CRI	>80

LTS

CDL 30.2040.02

Multi 30 (CDZ 3.62, 1xLED 22W 840/4000K 2230lm 75 °)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	955	955	955	955
15°	841	841	841	841
30°	507	507	507	507
45°	154	154	154	154
60°	7	7	7	7
75°	4	4	4	4
90°	0	0	0	0

cd / 1000 lm

Offset [m] Cone width [m] Illuminance [lx]


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	3.63	236.5
6.0	7.26	59.1
9.0	10.90	26.3
12.0	14.53	14.8
15.0	18.16	9.5

η	LED
Efficiency	101 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.3
UGR C90/C270	19.3
CIE Flux Codes	87 99 100 100 100
Ra/CRI	>80

LTS

Multi 30 (CDZ 3.63, 1xLED 22W 840/4000K 2220lm 75 °)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	1045	1045	1045	1045
15°	929	929	929	929
30°	495	495	495	495
45°	83	83	83	83
60°	26	26	26	26
75°	10	10	10	10
90°	1	1	1	1

cd / 1000 lm

Offset [m] Cone width [m] Illuminance [lx]


Offset [m]	Cone width [m]	Illuminance [lx]
3.0	3.35	257.7
6.0	6.70	64.4
9.0	10.06	28.6
12.0	13.41	16.1
15.0	16.76	10.3

η	LED
Efficiency	101 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.4
UGR C90/C270	19.4
CIE Flux Codes	88 97 99 100 100
Ra/CRI	>80

LTS

Multi 30 (CDZ 3.64, 1xLED 22W 840/4000K 2120lm 75 °)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	643	643	643	643
15°	557	557	557	557
30°	417	417	417	417
45°	246	246	246	246
60°	54	54	54	54
75°	26	26	26	26
90°	2	2	2	2

cd / 1000 lm

Offset [m] Cone width [m] Illuminance [lx]

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	4.90	151.6
6.0	9.81	37.9
9.0	14.71	16.8
12.0	19.62	9.5
15.0	24.52	6.1

η	LED
Efficiency	96 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	22 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	24.1
UGR C90/C270	24.1
CIE Flux Codes	69 92 98 100 100
Ra/CRI	>80

LTS

CDL 30.2040.02

Accessories



CDZ 3.01
partly frosted glass pane
(inside)



CDZ 3.08
satinated glass ring
(protruding)



CDZ 3.35
frosted decorative glass ring
(inside)



CDZ 3.38
satinated glass pane
(inside)



CDZ 3.39
clear glass pane
(inside)



CDZ 3.60
partly frosted acrylic glass pane
(inside)



CDZ 3.61
frosted acrylic glass pane
(inside)



CDZ 3.62
clear acrylic glass pane
(inside)



CDZ 3.63
frosted acrylic glass ring
(protruding)



CDZ 3.64
acrylic glass pane frosted in centre
(protruding)



NOL 50B/3H/DALI
LED emergency light-unit



ZVP 100
universal reinforcement frame
(module 625 x 625)