


LUNXXS 301.840.1/DALI



Colours	Article no.	EAN
silver	667372	4043544766861
black	667373	4043544766878
white	667374	4043544766885



Description

- can be used as ceiling, wall or pendant luminaire (suspension to be ordered separately)
- direct-indirect illumination without light-effect ring
- low indirect light component for ceiling lighting
- outstanding ease of maintenance
- no UV and thermal emissions
- luminaire consisting of sheet steel housing for ballast and light unit
- light unit can be separated from ballast housing without tools via bayonet catch (with safety rope)
- opal acrylic glass diffuser
- ballast housing for direct screw mounting
- 5-pole terminal block
- ballast (LED converter) integrated (with DALI dimming)

Standard options



Special options



Lighting data / Norms


Lamps	LED linear / CRI 80 / 4000 K
EPREL light sources	993701
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	17.0 W
Luminaire luminous flux	1470 lm
System efficiency	86.47 lm/W
Module efficiency	175.00 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights

Outer diameter	315 mm
Height	91 mm
Net weight	2.97 kg
Gross weight	3.12 kg

LUNXXS 301.840.1/DALI

Lunata XXSmall (1xLED 17W 840/4000K 1470lm)



	C0	C90	C180	C270
0°	340	340	340	340
15°	326	325	326	325
30°	288	287	288	287
45°	229	229	229	229
60°	152	152	152	152
75°	64	64	64	64
90°	1	1	1	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
3.0	9.17	9.16	55.5
6.0	18.34	18.32	13.9
9.0	27.51	27.49	6.2
12.0	36.67	36.65	3.5
15.0	45.84	45.81	2.2

η	LED
Efficiency	86 lm/W
Direct/Indirect	↓ 98% / ↑ 2%
System Power	17 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.6
UGR C90/C270	22.6
CIE Flux Codes	47 79 96 98 100
Ra/CRI	>80

LTS

Accessories



L 83/1500 DIM
wire-rope kit 3-fold
(length: 1500 mm, 5-core cable)



L 83/3000 DIM
wire-rope kit 3-fold
(length: 3000 mm, 5-core cable)



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOR
Organic Response sensor for surface mounting



ZB-OR-P SENSOR/3000
Organic Response sensor for pendant mounting