Pendant





IP20

LUZ-PT12 103.830.60/DALI-ST



Colours	Article no.	EAN
silver	666363	4043544756787
black	666364	4043544756794
white	666365	4043544756800





Description

• pendant luminaire in rectangular design for track mounting and diverse lighting tasks

CE

LED Modul / CRI 80 / 3000 K

L90 B50 50.000 h

L80 B50 100.000 h L80 B20 50.000 h

220 - 240 V / 50 - 60 Hz

22.7 W 3240 lm

≤25 Wide Flood

60°

IP20

T

142.73 lm/W 160.00 lm/W

- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- housing made from sheet steel
- protruding lens optics made from matt PMMA
- wire-rope suspension 2-fold with height adjustment and 3-phase track adapter DALI (ONETrack), (length: 1500 mm, cable transparent)
- ballast (LED converter) integrated (with DALI dimming)

Standard options



Special options



Lighting data / Norms

Lamps

Lifetime

System power Luminaire luminous flux System efficiency Module efficiency UGR class Beam range Beam angle Supply voltage Protection class Type of protection

Dimensions / Weights

87 mm
6 mm
6 mm
.47 kg
.55 kg


Pendant




LUZ-PT12 103.830.60/DALI-ST

LUZ-PT12 103.830.60/DALI-ST LUZ | Pendant Track (1xLED 23W 830/3000K 3240lm)

C0/C180 cd / 1000 lm ------ C90/C270



	C0	C90	C180	C270
0°	793	793	793	793
15°	863	866	863	866
30°	344	386	344	386
45°	112	119	112	119
60°	54	52	54	52
75°	36	27	36	27
90°	14	2	14	2
cd / 1000 lm				



η	LED 141 lm/W ↓ 98% / ↑ 2%		
Efficiency			
Direct/Indirect			
System Power	23 W		
UGR	X=4H, Y=8H		
Reflection factors	70/50/20		
UGR C0/C180	22.8		
UGR C90/C270	22.3		
CIE Flux Codes	76 90 96 98 100		
Ra/CRI	>80		

Accessories



ST-A 10/9000A-1-ST surface-mounted track ONETrack Advance with data bus (length: 1000 mm)



ST-A 20/9000A-2-ST surface-mounted track ONETrack Advance with data bus (length: 2000 mm)



ST-A 30/9000A-3-ST surface-mounted track ONETrack Advance with data bus (length: 3000 mm)



ST-A 40/9000A-4-ST surface-mounted track ONETrack Advance with data bus (length: 4000 mm)



ST-E 10/9000-1-R recessed track ONETrack with data bus (length: 1000 mm)



ST-E 20/9000-2-R recessed track ONETrack with data bus (length: 2000 mm)



ST-E 30/9000-3-R recessed track ONETrack with data bus (length: 3000 mm)



ST-E 40/9000-4-R recessed track ONETrack with data bus (length: 4000 mm)



ZB-OR DONGLE Organic Response IR dongle kit



ZB-OR GATEWAY Organic Response IoT Gateway Cascade Series



ZB-OR-T SENSOR Organic Response sensor for track mounting