

Pendant

LUZ-PT13 104.830.AS/DALI-ST



Colours	Article no.	EAN
silver	666724	4043544760388
black	666725	4043544760395
white	666726	4043544760401



Description

- pendant luminaire in rectangular design for track mounting and asymmetrical light distribution for wall illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- housing made from sheet steel
- protruding lens optics made from matt PMMA
- wire-rope suspension 2-fold with height adjustment and 3-phase track adapter DALI (ONETrack), (length: 1500 mm, cable transparent)
- ballast (LED converter) integrated (with DALI dimming)

Standard options



Special options



Lighting data / Norms

Lamps	LED Modul / CRI 80 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	33.6 W
Luminaire luminous flux	4810 lm
System efficiency	143.15 lm/W
Module efficiency	160.00 lm/W
UGR class	≤25
Beam range	Asymmetric
Beam angle	Asymmetric
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights

Length	873 mm
Width	66 mm
Height	46 mm
Net weight	2.00 kg
Gross weight	2.10 kg


Pendant

LUZ-PT13 104.830.AS/DALI-ST

LUZ-PT13 104.830.AS/DALI-ST

LUZ | Pendant Track (1xLED 34W 830/3000K 4810lm)

— C0/C180 cd / 1000 lm — C90/C270



	C0	C90	C180	C270
0°	495	495	495	495
15°	742	469	348	469
30°	600	327	165	327
45°	262	178	73	178
60°	91	85	56	85
75°	34	33	49	33
90°	13	1	15	1
cd / 1000 lm				

LDC unsuitable for cone representation.
Asymmetric LDC.

η	LED
Efficiency	141 lm/W
Direct/Indirect	↓ 99% / ↑ 1%
System Power	34 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	24.9
UGR C90/C270	24.4
CIE Flux Codes	65 88 97 99 100
Ra/CRI	>80

LTS

Accessories

**ST-A 10/9000A-1-ST**surface-mounted track ONETrack Advance with data bus
(length: 1000 mm)**ST-A 20/9000A-2-ST**surface-mounted track ONETrack Advance with data bus
(length: 2000 mm)**ST-A 30/9000A-3-ST**surface-mounted track ONETrack Advance with data bus
(length: 3000 mm)**ST-A 40/9000A-4-ST**surface-mounted track ONETrack Advance with data bus
(length: 4000 mm)**ST-E 10/9000-1-R**recessed track ONETrack with data bus
(length: 1000 mm)**ST-E 20/9000-2-R**recessed track ONETrack with data bus
(length: 2000 mm)**ST-E 30/9000-3-R**recessed track ONETrack with data bus
(length: 3000 mm)**ST-E 40/9000-4-R**recessed track ONETrack with data bus
(length: 4000 mm)**ZB-OR DONGLE**

Organic Response IR dongle kit

**ZB-OR GATEWAY**

Organic Response IoT Gateway Cascade Series

**ZB-OR-T SENSOR**

Organic Response sensor for track mounting