Pendant





IP20

LUZ-PT13 104.840.60/DALI-ST



Colours	Article no.	EAN
silver	666393	4043544757081
black	666394	4043544757098
white	666395	4043544757104





Description

• pendant luminaire in rectangular design for track mounting and diverse lighting tasks

CE

LED Modul/CRI 80/4000 K

L90 B50 50.000 h

L80 B50 100.000 h L80 B20 50.000 h

220 - 240 V / 50 - 60 Hz

33.6 W 5070 lm

≤25 Wide Flood

60°

IP20

T

150.89 lm/W 193.50 lm/W

- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- housing made from sheet steel
- protruding lens optics made from matt PMMA
- wire-rope suspension 2-fold with height adjustment and 3-phase track adapter DALI (ONETrack), (length: 1500 mm, cable transparent)
- · ballast (LED converter) integrated (with DALI dimming)

Standard options



Special options



Lighting data / Norms

Lamps

Lifetime

System power Luminaire luminous flux System efficiency Module efficiency UGR class Beam range Beam angle Supply voltage Protection class Type of protection

Dimensions / Weights

Length	873 mm
Width	66 mm
Height	46 mm
Net weight	2.00 kg
Gross weight	2.10 kg




Pendant




LUZ-PT13 104.840.60/DALI-ST

LUZ-PT13 104.840.60/DALI-ST

LUZ | Pendant Track (1xLED 34W 840/4000K 5070lm)



	C0	C90	C180	C270	
0°	800	800	800	800	
15°	887	857	887	857	
30°	342	377	342	377	
45°	112	117	112	117	
60°	54	50	54	50	
75°	34	25	34	25	
90°	13	1	13	1	
cd / 1000 lm					



η	LED 149 lm/W ↓ 99% / ↑ 1%	
Efficiency		
Direct/Indirect		
System Power	34 W	
UGR	X=4H, Y=8H	
Reflection factors	70/50/20	
UGR C0/C180	22.8	
UGR C90/C270	22.3	
CIE Flux Codes	76 90 97 99 100	
Ra/CRI	> 80	

Accessories



ST-A 10/9000A-1-ST surface-mounted track ONETrack Advance with data bus (length: 1000 mm)



ST-A 20/9000A-2-ST surface-mounted track ONETrack Advance with data bus (length: 2000 mm)



ST-A 30/9000A-3-ST surface-mounted track ONETrack Advance with data bus (length: 3000 mm)



ST-A 40/9000A-4-ST surface-mounted track ONETrack Advance with data bus (length: 4000 mm)



ST-E 10/9000-1-R recessed track ONETrack with data bus (length: 1000 mm)



ST-E 20/9000-2-R recessed track ONETrack with data bus (length: 2000 mm)



ST-E 30/9000-3-R recessed track ONETrack with data bus (length: 3000 mm)



ST-E 40/9000-4-R recessed track ONETrack with data bus (length: 4000 mm)



ZB-OR DONGLE Organic Response IR dongle kit



ZB-OR GATEWAY Organic Response IoT Gateway Cascade Series



ZB-OR-T SENSOR Organic Response sensor for track mounting