
### **Pendant**





# LUZ-PT14 103.840.60/DALI-ST



Colours	Article no.	EAN
silver	666405	4043544757203
black	666406	4043544757210
white	666407	4043544757227







# Description









- pendant luminaire in rectangular design for track mounting and diverse lighting tasks
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- · housing made from sheet steel
- protruding lens optics made from matt PMMA
- wire-rope suspension 2-fold with height adjustment and 3-phase track adapter DALI (ONETrack), (length: 1500 mm, cable transparent)
- · ballast (LED converter) integrated (with DALI dimming)

## Standard options



## Special options













# Lighting data / Norms

LED Modul/CRI 80 / 4000 K L90 B50 50.000 h

Lifetime L80 B50 100.000 h L80 B20 50.000 h

System power 21.5 W
Luminaire luminous flux 3410 lm
System efficiency 158.60 lm/W
Module efficiency 193.50 lm/W
UGR class ≤22
Beam range Wide Flood
Beam angle 60°

**Supply voltage** 220 - 240 V / 50 - 60 Hz

Protection class | Type of protection | IP20

# Dimensions / Weights

 Length
 1160 mm

 Width
 66 mm

 Height
 46 mm

 Net weight
 2.53 kg

 Gross weight
 2.66 kg


## **Pendant**




# LUZ-PT14 103.840.60/DALI-ST

## LUZ-PT14 103.840.60/DALI-ST

LUZ | Pendant Track (1xLED 22W 840/4000K 3410lm)



	C0	C90	C180	C270
0°	793	793	793	793
15°	861	864	861	864
30°	342	387	342	387
45°	112	120	112	120
60°	55	53	55	53
75°	36	27	36	27
90°	14	2	14	2
	cc	i / 1000 I	m	



η	LED 155 lm/W ↓ 98% / ↑ 2%	
Efficiency		
Direct/Indirect		
System Power	22 W	
UGR	X=4H, Y=8H	
Reflection factors	70/50/20	
UGR C0/C180	20.6	
UGR C90/C270	20.1	
CIE Flux Codes	76 90 96 98 100	
Ra/CRI	>80	

LTS

## **Accessories**



#### ST-A 10/9000A-1-ST

surface-mounted track ONETrack Advance with data bus

(length: 1000 mm)



#### ST-A 20/9000A-2-ST

surface-mounted track ONETrack Advance with data bus

(length: 2000 mm)



#### ST-A 30/9000A-3-ST

surface-mounted track ONETrack Advance with data bus

(length: 3000 mm)



#### ST-A 40/9000A-4-ST

surface-mounted track ONETrack Advance with data bus

(length: 4000 mm)



## ST-E 10/9000-1-R

recessed track ONETrack with data bus (length: 1000 mm)



## ST-E 20/9000-2-R

recessed track ONETrack with data bus (length: 2000 mm)



## ST-E 30/9000-3-R

recessed track ONETrack with data bus (length: 3000 mm)



## ST-E 40/9000-4-R

recessed track ONETrack with data bus (length: 4000 mm)



#### **ZB-OR DONGLE**

Organic Response IR dongle kit



#### **ZB-OR GATEWAY**

Organic Response IoT Gateway Cascade Series



#### ZB-OR-T SENSOR

Organic Response sensor for track mounting