
Pendant





LUZ-PT14 106.840.60/DALI-ST



Colours	Article no.	EAN
silver	666417	4043544757326
black	666418	4043544757333
white	666419	4043544757340







Description









- pendant luminaire in rectangular design for track mounting and diverse lighting tasks
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- · housing made from sheet steel
- protruding lens optics made from matt PMMA
- wire-rope suspension 2-fold with height adjustment and 3-phase track adapter DALI (ONETrack), (length: 1500 mm, cable transparent)
- · ballast (LED converter) integrated (with DALI dimming)

Standard options



Special options













Lighting data / Norms

LED Modul / CRI 80 / 4000 K L90 B50 50.000 h

Lifetime L80 B50 100.000 h L80 B20 50.000 h

Supply voltage 220 - 240 V / 50 - 60 Hz

Protection class | Type of protection | IP20

Dimensions / Weights

 Length
 1160 mm

 Width
 66 mm

 Height
 46 mm

 Net weight
 2.53 kg

 Gross weight
 2.66 kg


Pendant




LUZ-PT14 106.840.60/DALI-ST

LUZ-PT14 106.840.60/DALI-ST

LUZ | Pendant Track (1xLED 44W 840/4000K 6760lm)



	C0	C90	C180	C270
0°	800	800	800	800
15°	887	857	887	857
30°	342	377	342	377
45°	112	117	112	117
60°	54	50	54	50
75°	34	25	34	25
90°	13	1	13	1
cd / 1000 lm				



η	LED 154 lm/W ↓ 99% / ↑ 1%	
Efficiency		
Direct/Indirect		
System Power	44 W	
UGR	X=4H, Y=8H	
Reflection factors	70/50/20	
UGR C0/C180	22.8	
UGR C90/C270	22.3	
CIE Flux Codes	76 90 97 99 100	
Ra/CRI	>80	

LTS

Accessories



ST-A 10/9000A-1-ST

surface-mounted track ONETrack Advance with data bus (length: 1000 mm)



ST-A 20/9000A-2-ST

surface-mounted track ONETrack Advance with data bus

(length: 2000 mm)



ST-A 30/9000A-3-ST

surface-mounted track ONETrack Advance with data bus (length: 3000 mm)



ST-A 40/9000A-4-ST

surface-mounted track ONETrack Advance with data bus

(length: 4000 mm)



ST-E 10/9000-1-R

recessed track ONETrack with data bus (length: 1000 mm)



ST-E 20/9000-2-R

recessed track ONETrack with data bus (length: 2000 mm)



ST-E 30/9000-3-R

recessed track ONETrack with data bus (length: 3000 mm)



ST-E 40/9000-4-R

recessed track ONETrack with data bus (length: 4000 mm)



ZB-OR DONGLE

Organic Response IR dongle kit



ZB-OR GATEWAY

Organic Response IoT Gateway Cascade Series



ZB-OR-T SENSOR

Organic Response sensor for track mounting