
Pendant





LUZ-PT22 103.830.60/DALI-ST



Colours	Article no.	EAN
silver	666447	4043544757623
black	666448	4043544757630
white	666449	4043544757647







Description







- pendant luminaire in rectangular design for track mounting and diverse lighting tasks
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- · housing made from sheet steel
- protruding lens optics made from matt PMMA
- wire-rope suspension 2-fold with height adjustment and 3-phase track adapter DALI (ONETrack), (length: 1500 mm, cable transparent)
- · ballast (LED converter) integrated (with DALI dimming)

Standard options



Special options













Lighting data / Norms

Lamps LED Modul/CRI 80/3000 K L90 B50 50.000 h Lifetime L80 B50 100.000 h L80 B20 50.000 h System power 21.5 W Luminaire luminous flux 3270 lm System efficiency 152.09 lm/W 160.00 lm/W Module efficiency **UGR** class ≤22 Wide Flood Beam range

 Beam angle
 60°

 Supply voltage
 220 - 240 V / 50 - 60 Hz

Protection class | Type of protection | IP20

Dimensions / Weights

 Length
 587 mm

 Width
 130 mm

 Height
 46 mm

 Net weight
 2.56 kg

 Gross weight
 2.67 kg


Pendant




LUZ-PT22 103.830.60/DALI-ST

LUZ-PT22 103.830.60/DALI-ST

LUZ | Pendant Track (1xLED 22W 830/3000K 3270lm)



	C0	C90	C180	C270
0°	784	784	784	784
15°	876	863	876	863
30°	350	393	350	393
45°	116	124	116	124
60°	56	54	56	54
75°	32	28	32	28
90°	7	2	7	2
cd / 1000 lm				



η	LED 149 lm/W ↓ 99% / ↑ 1% 22 W	
Efficiency		
Direct/Indirect		
System Power		
UGR	X=4H, Y=8H	
Reflection factors	70/50/20	
UGR C0/C180	20.4	
UGR C90/C270	20.1	
CIE Flux Codes	76 90 97 99 100	
Ra/CRI	>80	

LTS

Accessories



ST-A 10/9000A-1-ST

surface-mounted track ONETrack Advance with data bus

(length: 1000 mm)



ST-A 20/9000A-2-ST

surface-mounted track ONETrack Advance with data bus

(length: 2000 mm)



ST-A 30/9000A-3-ST

surface-mounted track ONETrack Advance with data bus

(length: 3000 mm)



ST-A 40/9000A-4-ST

surface-mounted track ONETrack Advance with data bus

(length: 4000 mm)



ST-E 10/9000-1-R

recessed track ONETrack with data bus (length: 1000 mm)



ST-E 20/9000-2-R

recessed track ONETrack with data bus (length: 2000 mm)



ST-E 30/9000-3-R

recessed track ONETrack with data bus (length: 3000 mm)



ST-E 40/9000-4-R

recessed track ONETrack with data bus (length: 4000 mm)



ZB-OR DONGLE

Organic Response IR dongle kit



ZB-OR GATEWAY

Organic Response IoT Gateway Cascade Series



ZB-OR-T SENSOR

Organic Response sensor for track mounting