Pendant





IP20

LUZ-PT32 110.830.60/DALI-ST



758224
758231
758248





Description

• pendant luminaire in rectangular design for track mounting and diverse lighting tasks

CE

LED Modul/CRI 80/3000 K

L90 B50 50.000 h

64.8 W

9710 lm

≤25 Wide Flood

60°

I

IP20

149.84 lm/W

160.00 lm/W

220 - 240 V / 50 - 60 Hz

L80 B50 100.000 h L80 B20 50.000 h

- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- housing made from sheet steel
- protruding lens optics made from matt PMMA
- wire-rope suspension 2-fold with height adjustment and 3-phase track adapter DALI (ONETrack), (length: 1500 mm, cable transparent)
- · ballast (LED converter) integrated (with DALI dimming)

Standard options



Special options



Lighting data / Norms


Lamps

Lifetime

System power Luminaire luminous flux System efficiency Module efficiency UGR class Beam range Beam angle Supply voltage Protection class Type of protection

Dimensions / Weights

Length	587 mm
Width	193 mm
Height	46 mm
Netweight	3.22 kg
Gross weight	3.37 kg




Pendant




LUZ-PT32 110.830.60/DALI-ST

LUZ-PT32 110.830.60/DALI-ST

LUZ | Pendant Track (1xLED 65W 830/3000K 9710lm) C0/C180 cd / 1000 lm -C90/C270



	C0	C90	C180	C270		
0°	807	807	807	807		
15°	895	868	895	868		
30°	347	388	347	388		
45°	115	125	115	125		
60°	55	55	55	55		
75°	32	28	32	28		
90°	5	2	5	2		
cd / 1000 lm						



η	LEC		
Efficiency	149 lm/W		
Direct/Indirect	↓ 99% / ↑ 1%		
System Power	65 W		
UGR	X=4H, Y=8H		
Reflection factors	70/50/20		
UGR C0/C180	22.7		
UGR C90/C270	22.5		
CIE Flux Codes	76 90 97 99 100		
Ra/CRI	> 80		

Accessories



ST-A 10/9000A-1-ST surface-mounted track ONETrack Advance with data bus (length: 1000 mm)



ST-A 20/9000A-2-ST surface-mounted track ONETrack Advance with data bus (length: 2000 mm)



ST-A 30/9000A-3-ST surface-mounted track ONETrack Advance with data bus (length: 3000 mm)



ST-A 40/9000A-4-ST surface-mounted track ONETrack Advance with data bus (length: 4000 mm)



ST-E 10/9000-1-R recessed track ONETrack with data bus (length: 1000 mm)



ST-E 20/9000-2-R recessed track ONETrack with data bus (length: 2000 mm)



ST-E 30/9000-3-R recessed track ONETrack with data bus (length: 3000 mm)



ST-E 40/9000-4-R recessed track ONETrack with data bus (length: 4000 mm)



ZB-OR DONGLE Organic Response IR dongle kit



7B-OR GATEWAY Organic Response IoT Gateway Cascade Series



ZB-OR-T SENSOR Organic Response sensor for track mounting