


# LUZ-T13 104.830.AS



| Colours | Article no. | EAN |
|---|---|---|
| silver | 667225 | 4043544765390 |
| black | 667226 | 4043544765406 |
| white | 667227 | 4043544765413 |




## Description

- track-mounted luminaire in rectangular design with asymmetrical light distribution for wall illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- housing made from sheet steel
- protruding lens optics made from matt PMMA
- 3-phase track adapter
- ballast (LED converter) integrated

## Standard options




## Special options




## Lighting data / Norms

| | |
|---|---|
| **Lamps** | LED Modul / CRI 80 / 3000 K |
| **Lifetime** | L90 B50 50.000 h<br>L80 B50 100.000 h<br>L80 B20 50.000 h |
| **System power** | 34.0 W |
| **Luminaire luminous flux** | 4810 lm |
| **System efficiency** | 143.15 lm/W |
| **Module efficiency** | 160.00 lm/W |
| **UGR class** | ≤25 |
| **Beam angle** | Asymmetric |
| **Supply voltage** | 220 - 240 V / 50 - 60 Hz |
| **Protection class** | I |
| **Type of protection** | IP20 |


## Dimensions / Weights

| | |
|---|---|
| **Length** | 873 mm |
| **Width** | 66 mm |
| **Height** | 62 mm |
| **Net weight** | 1.77 kg |
| **Gross weight** | 1.87 kg |

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024

# LUZ-T13 104.830.AS

LUZ | Track-Mounted (1xLED 34W 830/3000K 4810lm)




| | C0 | C90 | C180 | C270 |
|---|---|---|---|---|
| 0° | 495 | 495 | 495 | 495 |
| 15° | 742 | 469 | 348 | 469 |
| 30° | 600 | 327 | 165 | 327 |
| 45° | 262 | 178 | 73 | 178 |
| 60° | 91 | 85 | 56 | 85 |
| 75° | 34 | 33 | 49 | 33 |
| 90° | 13 | 1 | 15 | 1 |

cd / 1000 lm

LDC unsuitable for cone representation.
Asymetric LDC.

| | |
|---|---|
| **η** | LED |
| Efficiency | 141 lm/W |
| Direct/Indirect | ↓ 99% / ↑ 1% |
| System Power | 34 W |
| **UGR** | X=4H, Y=8H |
| Reflection factors | 70/50/20 |
| UGR C0/C180 | 24.9 |
| UGR C90/C270 | 24.4 |
| CIE Flux Codes | 65 88 97 99 100 |
| Ra/CRI | >80 |

LTS

## Accessories



**ST-A 10/9000A-1-ST**
surface-mounted track ONETrack Advance with data bus
(length: 1000 mm)



**ST-A 20/9000A-2-ST**
surface-mounted track ONETrack Advance with data bus
(length: 2000 mm)



**ST-A 30/9000A-3-ST**
surface-mounted track ONETrack Advance with data bus
(length: 3000 mm)



**ST-A 40/9000A-4-ST**
surface-mounted track ONETrack Advance with data bus
(length: 4000 mm)



**ST-E 10/9000-1-R**
recessed track ONETrack with data bus
(length: 1000 mm)



**ST-E 20/9000-2-R**
recessed track ONETrack with data bus
(length: 2000 mm)



**ST-E 30/9000-3-R**
recessed track ONETrack with data bus
(length: 3000 mm)



**ST-E 40/9000-4-R**
recessed track ONETrack with data bus
(length: 4000 mm)

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024