APP 20.5040.1.2/DALI
















| Colours | Article no. | EAN |
|---------|-------------|---------------|
| black | 638580 | 4043544422590 |
| silver | 638581 | 4043544422606 |
| white | 638582 | 4043544422613 |







Description

- round pendant luminaire with direct-indirect lighting for balanced room ambience
- light component: direct 57% / indirect 43%
- outstanding ease of maintenance
- housing made from die-cast aluminium
- · design canopy (in luminaire colour) made from sheet steel
- height-adjustable Y-wire-rope suspension 3-fold (length: 2800 mm)
- transparent connecting cable
- diffuser made from prismatic acrylic glass with side-emitting LEDs (diffuser is completely transparent when switched off)
- easy screw mounting of the ceiling canopy
- luminaire ready-to-connect with ceiling canopy and feed-in
- ballast (LED converter DALI, dimmable) integrated in ceiling canopy

Standard options



Lighting data / Norms

 Lamps
 LED Modul / CRI 80 / 4000 K

 Lifetime
 L100 B50 50.000 h

 System power
 39.0 W

 System power
 39.0 W

 Luminaire luminous flux
 5140 lm

 System efficiency
 131.79 lm/W

 UGR class
 ≤19

Supply voltage 220 - 240 V / 50 - 60 Hz

Protection class I
Type of protection IP20

Dimensions / Weights

 Outer diameter
 675 mm

 Height
 31 mm

 Net weight
 7.08 kg

 Gross weight
 8.26 kg


Ceiling and Pendant Luminaires round · Appareo Round

LTS LOVE TO SHINE

APP 20.5040.1.2/DALI

APP 20.5040.1.2/DALI

Appareo Round (1xLED 39W 840/4000K 5140lm)



| | C0 | C90 | C180 | C270 |
|------|-----|----------|------|------|
| 0° | 199 | 199 | 199 | 199 |
| 30° | 158 | 158 | 158 | 158 |
| 60° | 82 | 79 | 82 | 79 |
| 90° | 2 | 2 | 2 | 2 |
| 120° | 115 | 110 | 115 | 110 |
| 150° | 36 | 36 | 36 | 36 |
| 180° | 30 | 30 | 30 | 30 |
| | co | 1 / 1000 | m | |

LDC unsuitable for cone representation.

The C0 angle is oversized.

| η | LED 132 lm/W ↓ 54% / ↑ 46% | | |
|--------------------|----------------------------------|--|--|
| Efficiency | | | |
| Direct/Indirect | | | |
| System Power | 39 W | | |
| UGR | X=4H, Y=8H | | |
| Reflection factors | 70/50/20 | | |
| UGR C0/C180 | 16.6 | | |
| UGR C90/C270 | 16.5 | | |
| CIE Flux Codes | 47 77 94 54 100 | | |
| Ra/CRI | >80 | | |

TS

Accessories



ZB-OR DONGLEOrganic Response IR dongle kit



ZB-OR GATEWAYOrganic Response IoT Gateway Cascade Series



ZB-OR-A SENSOROrganic Response sensor for surface mounting



ZB-OR-P SENSOR/3000Organic Response sensor for pendant mounting