


LUZ06-A 13.013.30



Colours	Article no.	EAN
black	655284	4043544640529
silver	655285	4043544640536
white	655286	4043544640543







Description

- linear luminaire for surface mounting
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- housing and partly integrated mounting box made from sheet steel
- tool-free snap-in and slide mechanism between housing and mounting box
- lens optics made from transparent high-gloss PMMA
- easy screw fixing of the mountig box
- 5-pole terminal block
- ballast (LED converter) integrated

Notes

For vertical mounting the weight force must point in the locking direction.

Standard options

4000 K

Special options

SCHWARZ · RAL · 3500 K · CRI 90 SDCM3 · TWL · DALI

Lighting data / Norms

Lamps	LED Matrix / CRI 85 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	36.0 W
Luminaire luminous flux	4750 lm
System efficiency	131.94 lm/W
Module efficiency	152.00 lm/W
UGR class	≤19
Beam angle	60°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights


Length	867 mm
Width	67 mm
Height	58 mm
Net weight	2.31 kg
Gross weight	2.70 kg

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024

LUZ06-A 13.013.30


LUZ06-A 13.013.30

LUZ | Surface-Mounted (1xLED 36W 830/3000K 4750lm)



	C0	C90	C180	C270
0°	749	749	749	749
15°	763	759	763	759
30°	546	535	546	535
45°	114	108	114	108
60°	30	20	30	20
75°	15	9	15	9
90°	4	1	4	1

cd / 1000 lm



η	LED
Efficiency	132 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	36 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.3
UGR C90/C270	18.7
CIE Flux Codes	85 96 99 100 100
Ra/CRI	>80

LTS

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024