



LUZ06-PA 13.007.40



Colours	Article no.	EAN
black	657162	4043544660572
silver	657163	4043544660589
white	657164	4043544660596



Description

- linear luminaire for pendant mounting
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- luminaire housing and partly integrated ballast housing made from sheet steel
- lens optics made from transparent high-gloss PMMA
- height-adjustable wire-rope suspension with ceiling box and feed-in (length: 1500 mm, cable transparent)
- ballast (LED converter) integrated

Standard options



Special options



Lighting data / Norms

Lamps	LED Matrix / CRI 85 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	18.0 W
Luminaire luminous flux	2470 lm
System efficiency	137.22 lm/W
Module efficiency	159.00 lm/W
UGR class	≤19
Beam angle	60°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Length	867 mm
Width	67 mm
Height	43 mm
Net weight	2.19 kg
Gross weight	2.31 kg

LUZ06-PA 13.007.40

LUZ06-PA 13.007.40

LUZ | Pendant (1xLED 18W 840/4000K 2470lm)



	C0	C90	C180	C270
0°	749	749	749	749
15°	763	759	763	759
30°	546	535	546	535
45°	114	108	114	108
60°	30	20	30	20
75°	15	9	15	9
90°	4	1	4	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	4.11	4.08	205.5
6.0	8.22	8.15	51.4
9.0	12.33	12.23	22.8
12.0	16.44	16.31	12.8
15.0	20.56	20.39	8.2

η	LED
Efficiency	137 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	18 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	17.0
UGR C90/C270	16.4
CIE Flux Codes	85 96 99 100 100
Ra/CRI	>80

LTS