



# LUZ06-PA 15.007.30



| Colours | Article no. | EAN |
|---|---|---|
| black | 657204 | 4043544660992 |
| silver | 657205 | 4043544661005 |
| white | 657206 | 4043544661012 |




## Description

- linear luminaire for pendant mounting
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- luminaire housing and partly integrated ballast housing made from sheet steel
- lens optics made from transparent high-gloss PMMA
- height-adjustable wire-rope suspension with ceiling box and feed-in (length: 1500 mm, cable transparent)
- ballast (LED converter) integrated

## Standard options

4000 K

## Special options

SCHWARZ | RAL | 3500 K | CRI 90 SDCM3 | TWL | DALI

## Lighting data / Norms

| | |
|---|---|
| Lamps | LED Matrix / CRI 85 / 3000 K |
| Lifetime | L90 B50 50.000 h<br>L80 B50 100.000 h<br>L80 B20 50.000 h |
| System power | 30.0 W |
| Luminaire luminous flux | 3960 lm |
| System efficiency | 132.00 lm/W |
| Module efficiency | 152.00 lm/W |
| UGR class | ≤19 |
| Beam angle | 60° |
| Supply voltage | 220 - 240 V / 50 - 60 Hz |
| Protection class | I |
| Type of protection | IP20 |

## Dimensions / Weights


| | |
|---|---|
| Length | 1439 mm |
| Width | 67 mm |
| Height | 43 mm |
| Net weight | 3.38 kg |
| Gross weight | 3.56 kg |

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024

# LUZ06-PA 15.007.30


**LUZ06-PA 15.007.30**

LUZ | Pendant (1xLED 30W 830/3000K 3960lm)




| | C0 | C90 | C180 | C270 |
|---|---|---|---|---|
| 0° | 749 | 749 | 749 | 749 |
| 15° | 763 | 759 | 763 | 759 |
| 30° | 546 | 535 | 546 | 535 |
| 45° | 114 | 108 | 114 | 108 |
| 60° | 30 | 20 | 30 | 20 |
| 75° | 15 | 9 | 15 | 9 |
| 90° | 4 | 1 | 4 | 1 |

cd / 1000 lm




| | |
|---|---|
| η | LED |
| Efficiency | 132 lm/W |
| Direct/Indirect | ↓ 100% / ↑ 0% |
| System Power | 30 W |
| **UGR** | X=4H, Y=8H |
| Reflection factors | 70/50/20 |
| UGR C0/C180 | 16.9 |
| UGR C90/C270 | 16.3 |
| CIE Flux Codes | 85 96 99 100 100 |
| Ra/CRI | >80 |

LTS

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024