



LUZ06-PA 15.013.40



Colours	Article no.	EAN
black	657222	4043544661173
silver	657223	4043544661180
white	657224	4043544661197



Description

- linear luminaire for pendant mounting
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- luminaire housing and partly integrated ballast housing made from sheet steel
- lens optics made from transparent high-gloss PMMA
- height-adjustable wire-rope suspension with ceiling box and feed-in (length: 1500 mm, cable transparent)
- ballast (LED converter) integrated

Standard options



Special options



Lighting data / Norms

Lamps	LED Matrix / CRI 85 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	60.0 W
Luminaire luminous flux	8220 lm
System efficiency	137.00 lm/W
Module efficiency	159.00 lm/W
UGR class	≤19
Beam angle	60°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Length	1439 mm
Width	67 mm
Height	43 mm
Net weight	3.38 kg
Gross weight	3.56 kg

LUZ06-PA 15.013.40

LUZ06-PA 15.013.40

LUZ | Pendant (1xLED 60W 840/4000K 8220lm)



	C0	C90	C180	C270
0°	749	749	749	749
15°	763	759	763	759
30°	546	535	546	535
45°	114	108	114	108
60°	30	20	30	20
75°	15	9	15	9
90°	4	1	4	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	4.11	4.08	683.7
6.0	8.22	8.15	170.9
9.0	12.33	12.23	76.0
12.0	16.44	16.31	42.7
15.0	20.56	20.39	27.3

η	LED
Efficiency	137 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	60 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.4
UGR C90/C270	18.8
CIE Flux Codes	85 96 99 100 100
Ra/CRI	>80

LTS