




LUZ06-T 13.013.30



Colours	Article no.	EAN
black	656292	4043544651006
silver	656293	4043544651013
white	656294	4043544651020



Description

- linear luminaire for 3-phase tracks
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- luminaire housing and partly integrated ballast housing made from sheet steel
- lens optics made from transparent high-gloss PMMA
- 3-phase track adapter
- ballast (LED converter) integrated

Standard options



Special options



Lighting data / Norms

Lamps

LED Matrix / CRI 85 / 3000 K

Lifetime

 L90 B50 50.000 h
 L80 B50 100.000 h
 L80 B20 50.000 h

System power

36.0 W

Luminaire luminous flux

4750 lm

System efficiency

131.94 lm/W

Module efficiency

152.00 lm/W

UGR class

≤19

Beam angle

60°

Supply voltage

220 - 240 V / 50 - 60 Hz

Protection class

I

Type of protection

IP20

Dimensions / Weights

Length

867 mm

Width

67 mm

Height

62 mm

Net weight

1.99 kg

Gross weight


2.17 kg

Workstation Luminaires

LUZ06-T 13.013.30

LUZ06-T 13.013.30

LUZ | Track-Mounted (1xLED 36W 830/3000K 4750lm)



	C0	C90	C180	C270
0°	749	749	749	749
15°	763	759	763	759
30°	546	535	546	535
45°	114	108	114	108
60°	30	20	30	20
75°	15	9	15	9
90°	4	1	4	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	4.11	4.08	395.1
6.0	8.22	8.15	98.8
9.0	12.33	12.23	43.9
12.0	16.44	16.31	24.7
15.0	20.56	20.39	15.8

η	LED
Efficiency	132 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	36 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.3
UGR C90/C270	18.7
CIE Flux Codes	85 96 99 100 100
Ra/CRI	>80

LTS

Accessories



ST-A 10/9000A-1-ST
surface-mounted track ONETrack Advance with data bus
(length: 1000 mm)



ST-A 20/9000A-2-ST
surface-mounted track ONETrack Advance with data bus
(length: 2000 mm)



ST-A 30/9000A-3-ST
surface-mounted track ONETrack Advance with data bus
(length: 3000 mm)



ST-A 40/9000A-4-ST
surface-mounted track ONETrack Advance with data bus
(length: 4000 mm)



ST-E 10/9000-1-R
recessed track ONETrack with data bus
(length: 1000 mm)



ST-E 20/9000-2-R
recessed track ONETrack with data bus
(length: 2000 mm)



ST-E 30/9000-3-R
recessed track ONETrack with data bus
(length: 3000 mm)



ST-E 40/9000-4-R
recessed track ONETrack with data bus
(length: 4000 mm)