


ML-A 045.0730.11 AOB/DALI



Colours	Article no.	EAN
silver anodised	663042	4043544721075
black	663043	4043544721082
white	663044	4043544721099



Description

- linear luminaire for direct ceiling or suspended mounting
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- wire-rope suspensions (with feed-in) to be ordered separately
- housing made from aluminium
- end covers made from die-cast zinc
- opal flush acrylic glass diffuser with profile guide and tool-free snap-in technology
- direct ceiling mounting via screw fixing
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $dT = 10$ Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options



Special options



Lighting data / Norms


Lamps	LED linear / CRI 80 / 3000 K
EPREL light sources	833899
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	
System power	16.4 W
Luminaire luminous flux	1610 lm
System efficiency	98.17 lm/W
Module efficiency	179.70 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP40

Dimensions / Weights


Length	1136 mm
Width	45 mm
Height	60 mm
Net weight	1.77 kg
Gross weight	1.89 kg

ML-A 045.0730.11 AOB/DALI

Monoline 045 | Surface-Mounted & Pendant (1xLED 16W 830/3000K 1610lm)



Offset [m] Cone width [m] Illuminance [lx]



η

Efficiency LED 101 lm/W

Direct/Indirect ↓ 100% / ↑ 0%

System Power 16 W

UGR

Reflection factors X=4H, Y=8H 70/50/20

UGR C0/C180 24.1

UGR C90/C270 24.4

CIE Flux Codes 50 81 96 100 100

Ra/CRI >80

Accessories



LK-Z045.103.03/DIM
wire-rope kit with feed-in DALI
(5-core, length: 3000 mm)



LK-Z045.103.05/DIM
wire-rope kit with feed-in DALI
(5-core, length: 5000 mm)



LK-Z045.104.03
wire-rope kit without feed-in
(length: 3000 mm)



LK-Z045.104.05
wire-rope kit without feed-in
(length: 5000 mm)



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOR
Organic Response sensor for surface mounting



ZB-OR-P SENSOR/3000
Organic Response sensor for pendant mounting