

ML-A 045.0740.08 APB/DALI



Description

- linear luminaire for direct ceiling or suspended mounting
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- wire-rope suspensions (with feed-in) to be ordered separately
- housing made from aluminium
- end covers made from die-cast zinc
- prismatic flush acrylic glass diffuser with profile guide and tool-free snap-in technology
- direct ceiling mounting via screw fixing
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $dT = 10$ Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options



Special options






Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.3 W
Luminaire luminous flux	1170 lm
System efficiency	95.12 lm/W
Module efficiency	164.17 lm/W
UGR class	≤22
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP40

Dimensions / Weights

Length	855 mm
Width	45 mm
Height	60 mm
Net weight	1.50 kg
Gross weight	1.59 kg


Colours	Article no.	EAN
silver anodised	663000	4043544720658
black	663001	4043544720665
white	663002	4043544720672



Mounted

ML-A 045.0740.08 APB/DALI

Monoline 045 | Surface-Mounted & Pendant (1xLED 12W 840/4000K 1170lm)



	C0	C90	C180	C270
0°	569	569	569	569
15°	531	547	531	547
30°	331	463	331	463
45°	176	275	176	275
60°	78	98	78	98
75°	31	31	31	31
90°	0	0	0	0

cd / 1000 lm

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	4.04 5.89	73.9
6.0	8.08 11.78	18.5
9.0	12.12 17.67	8.2
12.0	16.16 23.56	4.6
15.0	20.19 29.45	3.0

η	LED
Efficiency	98 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.4
UGR C90/C270	21.2
CIE Flux Codes	65 90 98 100 100
Ra/CRI	> 80

LTS


Accessories



LK-Z045.103.03/DIM
 wire-rope kit with feed-in DALI
 (5-core, length: 3000 mm)



LK-Z045.103.05/DIM
 wire-rope kit with feed-in DALI
 (5-core, length: 5000 mm)



LK-Z045.104.03
 wire-rope kit without feed-in
 (length: 3000 mm)



LK-Z045.104.05
 wire-rope kit without feed-in
 (length: 5000 mm)



ZB-OR DONGLE
 Organic Response IR dongle kit



ZB-OR GATEWAY
 Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOR
 Organic Response sensor for surface mounting



ZB-OR-P SENSOR/3000
 Organic Response sensor for pendant mounting