




Mounted

ML-A 045.1040.08 APB



Colours	Article no.	EAN
silver anodised	663033	4043544720986
black	663034	4043544720993
white	663035	4043544721006



Description

- linear luminaire for direct ceiling or suspended mounting
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- wire-rope suspensions (with feed-in) to be ordered separately
- housing made from aluminium
- end covers made from die-cast zinc
- prismatic flush acrylic glass diffuser with profile guide and tool-free snap-in technology
- direct ceiling mounting via screw fixing
- 5-pole terminal block
- ballast (LED converter) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at $dT = 10$ Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options



Special options



Lighting data / Norms


Lamps	LED linear / CRI 80 / 4000 K
EPREL light sources	833900 833895
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	
System power	19.3 W
Luminaire luminous flux	1880 lm
System efficiency	97.40 lm/W
Module efficiency	187.83 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP40

Dimensions / Weights

Length	855 mm
Width	45 mm
Height	60 mm
Net weight	1.44 kg
Gross weight	1.53 kg

ML-A 045.1040.08 APB

Monoline 045 | Surface-Mounted & Pendant (1xLED 19W 840/4000K 1880lm)



Offset [m]	Cone width [m]	Illuminance [lx]
3.0	4.04 5.89	118.8
6.0	8.08 11.78	29.7
9.0	12.12 17.67	13.2
12.0	16.16 23.56	7.4
15.0	20.19 29.45	4.8

C0-C180 Plane C90-C270 Plane

η	LED
Efficiency	99 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	19 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.0
UGR C90/C270	22.9
CIE Flux Codes	65 90 98 100 100
Ra/CRI	>80

LTS

Accessories



LK-Z045.103.03
wire-rope kit with feed-in
(length: 3000 mm, 3-core)



LK-Z045.103.05
wire-rope kit with feed-in
(length: 5000 mm, 3-core)



LK-Z045.104.03
wire-rope kit without feed-in
(length: 3000 mm)



LK-Z045.104.05
wire-rope kit without feed-in
(length: 5000 mm)