
Mounted





ML-A 070.0730.11 AOB/DALI



Colours	Article no.	EAN
silver anodised	653602	4043544623324
black	653603	4043544623331
white	653604	4043544623348







Description







IP40

- Inear luminaire for direct ceiling, wall or suspended mounting
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- outstanding ease of maintenand
- no UV and thermal emissions
- wire-rope suspensions (with feed-in) or wall bracket (2 pieces) to be ordered separately
- · housing made from aluminium
- end covers made from die-cast zinc
- opal flush acrylic glass diffuser with profile guide and tool-free snap-in technology
- direct ceiling or wall mounting via screw fixing
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at dT = 10 Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options



Special options











Lighting data / Norms

 Lamps
 LED linear / CRI 80 / 3000 K

 EPREL light sources
 833877

 L90 B50 50.000 h
 L80 B50 100.000 h

 L80 B20 50.000 h
 L80 B20 50.000 h

 System power
 12.5 W

 System power
 12.5 W

 Luminaire luminous flux
 1200 lm

 System efficiency
 96.00 lm/W

 Module efficiency
 178.36 lm/W

 UGR class
 ≤22

Supply voltage 220 - 240 V / 50 - 60 Hz

Protection class I
Type of protection IP40

Dimensions / Weights


Length1136 mmWidth70 mmHeight80 mmNet weight3.66 kgGross weight4.09 kg

Mounted




ML-A 070.0730.11 AOB/DALI

Monoline 070 Surface-Mounted & Pendant (1xLED 13W 830/3000K 1200lm)



	C0	C90	C180	C270
0°	372	372	372	372
15°	345	353	345	353
30°	296	303	296	303
45°	229	234	229	234
60°	149	153	149	153
75°	66	65	66	65
90°	1	1	1	1
cd / 1000 lm				



LED 92 lm/W		
		↓ 100% / ↑ 0%
13 W		
X=4H, Y=8H		
70/50/20		
22.3		
22.2		
48 79 96 100 100		
>80		

LTC

Accessories



LK-Z 070.103.03/DIM wire-rope kit with feed-in DALI (5-core, length: 3000 mm)



LK-Z 070.103.05/DIM wire-rope kit with feed-in DALI (5-core, length: 5000 mm)



LK-Z 070.104.03 wire-rope kit without feed-in (length: 3000 mm)



LK-Z 070.104.05 wire-rope kit without feed-in (length: 5000 mm)



LK-Z 070.114 wall bracket (1 piece)



ZB-OR DONGLEOrganic Response IR dongle kit



ZB-OR GATEWAYOrganic Response IoT Gateway Cascade Series



ZB-OR-A SENSOROrganic Response sensor for surface mounting



ZB-OR-P SENSOR/3000Organic Response sensor for pendant mounting