


ML-A 070.0740.14 AOB



Colours	Article no.	EAN
silver anodised	653671	4043544624017
black	653672	4043544624024
white	653673	4043544624031







Description

- linear luminaire for direct ceiling, wall or suspended mounting
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- wire-rope suspensions (with feed-in) or wall bracket (2 pieces) to be ordered separately
- housing made from aluminium
- end covers made from die-cast zinc
- opal flush acrylic glass diffuser with profile guide and tool-free snap-in technology
- direct ceiling or wall mounting via screw fixing
- 5-pole terminal block
- ballast (LED converter) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at dT = 10 Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options

3000 K | DALI

Special options

RAL | 2700 K

Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
EPREL light sources	833873|833878
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	16.0 W
Luminaire luminous flux	1560 lm
System efficiency	100.00 lm/W
Module efficiency	187.99 lm/W
UGR class	≤22
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP40


Dimensions / Weights

Length	1416 mm
Width	70 mm
Height	80 mm
Net weight	4.30 kg
Gross weight	4.83 kg

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024


ML-A 070.0740.14 AOB

Monoline 070 Surface-Mounted & Pendant (1xLED 16W 840/4000K 1560lm)



	C0	C90	C180	C270
0°	368	368	368	368
15°	349	350	349	350
30°	296	300	296	300
45°	227	233	227	233
60°	148	154	148	154
75°	66	66	66	66
90°	1	1	1	1

cd / 1000 lm



η	LED
Efficiency	98 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	16 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.4
UGR C90/C270	22.4
CIE Flux Codes	48 79 96 100 100
Ra/CRI	>80

LTS

Accessories



LK-Z070.103.03
wire-rope kit with feed-in
(3-core, length: 3000 mm)



LK-Z070.103.05
wire-rope kit with feed-in
(3-core, length: 5000 mm)



LK-Z070.104.03
wire-rope kit without feed-in
(length: 3000 mm)



LK-Z070.104.05
wire-rope kit without feed-in
(length: 5000 mm)



LK-Z070.114
wall bracket
(1 piece)

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024