


ML-A 070.1030.08 APB/DALI



Colours	Article no.	EAN
silver anodised	663415	4043544724793
black	663416	4043544724809
white	663417	4043544724816







Description

- linear luminaire for direct ceiling, wall or suspended mounting
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- wire-rope suspensions (with feed-in) or wall bracket (2 pieces) to be ordered separately
- housing made from aluminium
- end covers made from die-cast zinc
- prismatic flush acrylic glass diffuser with profile guide and tool-free snap-in technology
- direct ceiling or wall mounting via screw fixing
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at dT = 10 Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

Standard options

4000 K

Special options

RAL · 2700 K · CRI 90 SDCM3 · TWL · TWPI

Lighting data / Norms


Lamps	LED linear / CRI 80 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	14.0 W
Luminaire luminous flux	1240 lm
System efficiency	90.51 lm/W
Module efficiency	156.66 lm/W
UGR class	≤22
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP40

Dimensions / Weights

Length	855 mm
Width	70 mm
Height	80 mm
Net weight	2.86 kg
Gross weight	3.18 kg


ML-A 070.1030.08 APB/DALI

Monoline 070 Surface-Mounted & Pendant (1xLED 14W 830/3000K 1240lm)



	C0	C90	C180	C270
0°	579	579	579	579
15°	557	559	557	559
30°	329	483	329	483
45°	172	277	172	277
60°	69	93	69	93
75°	27	29	27	29
90°	0	0	0	0

cd / 1000 lm



η	LED
Efficiency	89 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	14 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	18.5
UGR C90/C270	19.8
CIE Flux Codes	66 90 98 100 100
Ra/CRI	>80

LTS

Accessories



LK-Z 070.103.03/DIM
wire-rope kit with feed-in DALI
(5-core, length: 3000 mm)



LK-Z 070.103.05/DIM
wire-rope kit with feed-in DALI
(5-core, length: 5000 mm)



LK-Z 070.104.03
wire-rope kit without feed-in
(length: 3000 mm)



LK-Z 070.104.05
wire-rope kit without feed-in
(length: 5000 mm)



LK-Z 070.114
wall bracket
(1 piece)




ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOR
Organic Response sensor for surface mounting



ZB-OR-P SENSOR/3000
Organic Response sensor for pendant mounting

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 29.03.2024