




# ML-A 070.1030.14 APB/DALI



Colours	Article no.	EAN
silver anodised	663469	4043544725332
black	663470	4043544725349
white	663471	4043544725356



## Description

- linear luminaire for direct ceiling, wall or suspended mounting
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- wire-rope suspensions (with feed-in) or wall bracket (2 pieces) to be ordered separately
- housing made from aluminium
- end covers made from die-cast zinc
- prismatic flush acrylic glass diffuser with profile guide and tool-free snap-in technology
- direct ceiling or wall mounting via screw fixing
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

## Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at  $\Delta T = 10$  Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

## Standard options



## Special options



## Lighting data / Norms

<b>Lamps</b>	LED linear / CRI 80 / 3000 K
<b>EPREL light sources</b>	833877 833872
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
<b>Lifetime</b>	
<b>System power</b>	22.8 W
<b>Luminaire luminous flux</b>	2060 lm
<b>System efficiency</b>	90.35 lm/W
<b>Module efficiency</b>	179.94 lm/W
<b>UGR class</b>	≤22
<b>Supply voltage</b>	220 - 240 V / 50 - 60 Hz
<b>Protection class</b>	I
<b>Type of protection</b>	IP40


## Dimensions / Weights

<b>Length</b>	1416 mm
<b>Width</b>	70 mm
<b>Height</b>	80 mm
<b>Net weight</b>	4.36 kg
<b>Gross weight</b>	4.89 kg

## Mounted

## ML-A 070.1030.14 APB/DALI

Monoline 070 Surface-Mounted &amp; Pendant (1xLED 23W 830/3000K 2060lm)



## Accessories



**LK-Z 070.103.03/DIM**  
 wire-rope kit with feed-in DALI  
 (5-core, length: 3000 mm)



**LK-Z 070.103.05/DIM**  
 wire-rope kit with feed-in DALI  
 (5-core, length: 5000 mm)



**LK-Z 070.104.03**  
 wire-rope kit without feed-in  
 (length: 3000 mm)



**LK-Z 070.104.05**  
 wire-rope kit without feed-in  
 (length: 5000 mm)



**LK-Z 070.114**  
 wall bracket  
 (1 piece)



**ZB-OR DONGLE**  
 Organic Response IR dongle kit



**ZB-OR GATEWAY**  
 Organic Response IoT Gateway Cascade Series



**ZB-OR-A SENSOR**  
 Organic Response sensor for surface mounting



**ZB-OR-P SENSOR/3000**  
 Organic Response sensor for pendant mounting