
#### Mounted





## ML-A 070.1130.14 APB/DALI



Colours	Article no.	EAN
silver anodised	653848	4043544625786
black	653849	4043544625793
white	653850	4043544625809







## Description







- · linear luminaire for direct ceiling, wall or suspended mounting
- symmetrical light distribution and illumination
- outstanding ease of maintenance
- no UV and thermal emissions
- wire-rope suspensions (with feed-in) or wall bracket (2 pieces) to be ordered separately
- housing made from aluminium
- end covers made from die-cast zinc
- prismatic flush acrylic glass diffuser with profile guide and tool-free snap-in technology
- direct ceiling or wall mounting via screw fixing
- 5-pole terminal block
- ballast (LED converter DALI, dimmable) integrated

#### **Notes**

The linear thermal expansion of the aluminium profile is about  $0.3 \, \text{mm}$  per meter at dT = 10 Kelvin. IP40 only applies in combination with mounted acrylic glass diffuser mounted acrylic glass profile.

## Standard options



#### Special options











## Lighting data / Norms

Lamps LED linear / CRI 80 / 3000 K **EPREL light sources** 833899|833894 L90 B50 50.000 h Lifetime L80 B50 100.000 h L80 B20 50.000 h System power 55.0 W Luminaire luminous flux 5010 lm System efficiency 91.09 lm/W Module efficiency 178.58 lm/W **UGR** class <25 Supply voltage 220 - 240 V / 50 - 60 Hz

Protection class I
Type of protection IP40

## Dimensions / Weights

 Length
 1416 mm

 Width
 70 mm

 Height
 80 mm

 Net weight
 4.36 kg


 Gross weight
 4.89 kg

#### Mounted




# ML-A 070.1130.14 APB/DALI

Monoline 070 Surface-Mounted & Pendant (1xLED 55W 830/3000K 5010lm)



	C0	C90	C180	C270
0°	556	556	556	556
15°	541	539	541	539
30°	332	485	332	485
45°	193	297	193	297
60°	74	116	74	116
75°	24	27	24	27
90°	0	0	0	0



η	LED		
Efficiency	91 lm/W		
Direct/Indirect	↓ 100% / ↑ 0%		
System Power	55 W		
UGR	X=4H, Y=8H		
Reflection factors	70/50/20		
UGR C0/C180	21.5		
UGR C90/C270	22.7		
CIE Flux Codes	66 91 99 100 100		
Ra/CRI	>80		

LTS

#### Accessories



LK-Z 070.103.03/DIM wire-rope kit with feed-in DALI (5-core, length: 3000 mm)



LK-Z 070.103.05/DIM wire-rope kit with feed-in DALI (5-core, length: 5000 mm)



LK-Z 070.104.03 wire-rope kit without feed-in (length: 3000 mm)



LK-Z 070.104.05 wire-rope kit without feed-in (length: 5000 mm)



LK-Z 070.114 wall bracket (1 piece)



**ZB-OR DONGLE** Organic Response IR dongle kit



**ZB-OR GATEWAY**Organic Response IoT Gateway Cascade Series



**ZB-OR-A SENSOR**Organic Response sensor for surface mounting



**ZB-OR-P SENSOR/3000**Organic Response sensor for pendant mounting