

48 V

# NEO-ORYO-T 101.940.15/DALI




## Description

- flexible filigree track-mounted spotlight with slightly conical light-head for 48 V track system
- light-head rotates through 355° and pivots through 90° via integrated articulated arm
- outstanding ease of maintenance
- no UV and thermal emissions
- anti-glare shield and decorative anti-glare ring available as accessories
- light-head made from die-cast aluminium
- innovative thermal management with design-integrated passive cooling
- high performance specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- black internal thermoplastic front ring
- clear acrylic safety glass
- 48 V track adapter with integrated DALI ballast

## Standard options



Colours	Article no.	EAN
black	652375	4043544610928
white	652376	4043544610935





## Lighting data / Norms

Lamps	LED Spot / CRI 90 / 4000 K
Lifetime	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
System power	21.2 W
Luminaire luminous flux	1540 lm
System efficiency	72.64 lm/W
Module efficiency	138.79 lm/W
UGR class	≤22
Beam range	Spot
Beam angle	15°
Protection class	II
Type of protection	IP20

## Dimensions / Weights

Length	177 mm
Width	66 mm
Height	79 mm
Diameter of light head	66 mm
Net weight	0.46 kg
Gross weight	0.56 kg




48 V

# NEO-ORYO-T 101.940.15/DALI

## NEO-ORYO-T 101.940.15/DALI

NeoORYO 100 | Track-Mounted | 48 V (1xLED 21W 940/4000K 1540lm)



## Accessories



**NEO-A 10/9500-1/ST6-E**  
 48 V surface-mounted track NeoLine with data bus  
 (length: 1000 mm)



**NEO-A 20/9500-2/ST6-E**  
 48 V surface-mounted track NeoLine with data bus  
 (length: 2000 mm)



**NEO-A 30/9500-3/ST6-E**  
 48 V surface-mounted track NeoLine with data bus  
 (length: 3000 mm)



**NEO-Z CONV 1X150**  
 power supply for 48 V systems 1x150 W



**NEO-Z CONV 1X150/CAS**  
 power supply for 48 V systems 1x150 W with  
 Casambi technology for wireless light control



**NEO-Z CONV 2X150**  
 power supply for 48 V systems 2x150 W



**NEO-Z CONV 2X150/CAS**  
 power supply for 48 V systems 2x150 W with  
 Casambi technology for wireless light control



**ZB-AGS 001**  
 anti-glare shield



**ZB-DAR 001**  
 decorative anti-glare ring



**ZBW 88**  
 honeycomb louvre