



OPT-R 104.0600.830/DALI



Colours	Article no.	EAN
white	661185	4043544700391



Description

- insert luminaire for suspended ceiling systems with visible T profile module (600 x 600)
- homogeneous lighting surface
- sound-absorbing surface (sound absorption level = 0.5)
- innovative tube technology for glare-free illumination
- advanced lens optics with a standard beam angle of 60°
- no UV and thermal emissions
- outstanding ease of maintenance
- luminaire housing made from aluminium with micropoint optics
- tool-free mounting into ceiling
- pre-fabricated for mains connection
- ballast (LED converter) included (with DALI dimming)

Standard options



Special options



Lighting data / Norms


Lamps	LED Matrix / CRI 80 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	42.0 W
Luminaire luminous flux	4340 lm
System efficiency	103.33 lm/W
Module efficiency	174.00 lm/W
UGR class	≤16
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights


Length	592 mm
Width	592 mm
Height	50 mm
Recessed depth	150 mm
Net weight	4.74 kg
Gross weight	4.99 kg

OPT-R 104.0600.830/DALI

Optico | Recessed (1xLED 42W 830/3000K 4340lm)



	C0	C90	C180	C270
0°	1029	1029	1029	1029
15°	924	927	924	927
30°	491	498	491	498
45°	115	109	115	109
60°	22	21	22	21
75°	2	2	2	2
90°	0	0	0	0
cd / 1000 lm				



η	LED
Efficiency	103 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	42 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	12.4
UGR C90/C270	12.3
CIE Flux Codes	88 99 100 100 100
Ra/CRI	>80

LTS