




PLL 25.0475.840.2/DALI



Colours	Article no.	EAN
	633932	4043544359285



Description

- recessed light field with round design and flush and trimless ceiling look for homogeneous lighting and seamless integration in architecture projects
- no UV and thermal emissions
- sheet steel housing with removable LED unit
- adjustable ceiling thickness
- microprismatic insert pane with matt foil made from acrylic glass
- plasterboard mounting via drywall screws (mounting aid can be ordered optionally)
- 5-pole terminal block
- ballast (LED converter) integrated (with DALI dimming)

Notes

Required installation space: D = 625 mm. Flush plastering of the luminaire is required. Pretreat the plaster zone on the luminaire and ceiling with suitable adhesion primer.

Standard options



Special options



Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
EPREL light sources	833873
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	
System power	31.4 W
Luminaire luminous flux	2520 lm
System efficiency	80.25 lm/W
Module efficiency	190.00 lm/W
UGR class	≤22
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Outer diameter	475 mm
Height	121 mm
Cut-out (Ø)	480 mm
Ceiling thickness	10.0 - 30.0 mm
Recessed depth	151 mm
Net weight	5.24 kg
Gross weight	6.06 kg

PLL 25.0475.840.2/DALI

PLL 25.0475.840.2/DALI

PL 25 (1xLED 31W 840/4000K 2520lm)



	C0	C90	C180	C270
0°	460	460	460	460
15°	438	437	438	437
30°	381	381	381	381
45°	238	237	238	237
60°	108	117	108	117
75°	43	45	43	45
90°	1	1	1	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	6.18	6.23	128.7
6.0	12.36	12.47	32.2
9.0	18.54	18.70	14.3
12.0	24.72	24.94	8.0
15.0	30.90	31.17	5.1

η	LED
Efficiency	81 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	31 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.4
UGR C90/C270	19.5
CIE Flux Codes	60 87 97 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting



ZBMH 475
mounting aid for PLL 25.475...