




PLL 25.0675.830.1/DALI



Colours	Article no.	EAN
	633933	4043544359292



Description

- recessed light field with round design and flush and trimless ceiling look for homogeneous lighting and seamless integration in architecture projects
- no UV and thermal emissions
- sheet steel housing with removable LED unit
- adjustable ceiling thickness
- opal insert pane made from acrylic glass
- plasterboard mounting via drywall screws (mounting aid can be ordered optionally)
- 5-pole terminal block
- ballast (LED converter) integrated (with DALI dimming)

Notes

Required installation space: D = 825 mm. Flush plastering of the luminaire is required. Pretreat the plaster zone on the luminaire and ceiling with suitable adhesion primer.

Standard options



Special options



Lighting data / Norms

Lamps	LED linear / CRI 80 / 3000 K
EPREL light sources	833872 833877
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	
System power	66.7 W
Luminaire luminous flux	7130 lm
System efficiency	106.89 lm/W
Module efficiency	179.94 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights


Outer diameter	675 mm
Height	121 mm
Cut-out (Ø)	680 mm
Ceiling thickness	10.0 - 30.0 mm
Recessed depth	151 mm
Net weight	9.26 kg
Gross weight	10.88 kg

PLL 25.0675.830.1/DALI

PLL 25.0675.830.1/DALI

PL 25 (1xLED 67W 830/3000K 7130lm)

C0/C180 cd / 1000 lm C90/C270



	C0	C90	C180	C270
0°	355	355	355	355
15°	340	339	340	339
30°	298	297	298	297
45°	234	234	234	234
60°	154	155	154	155
75°	65	65	65	65
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

	C0-C180 Plane	C90-C270 Plane	
3.0	8.88 8.86		281.2
6.0	17.76 17.72		70.3
9.0	26.64 26.59		31.2
12.0	35.53 35.45		17.6
15.0	44.41 44.31		11.2

η	LED
Efficiency	106 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	67 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.9
UGR C90/C270	22.9
CIE Flux Codes	47 79 96 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting



ZBMH 675
mounting aid for PLL 25.675...