




PLL 26.0385.830.1/DALI



Colours	Article no.	EAN
silver	640111	4043544439451
white	640112	4043544439468
black	642212	4043544480019



Description

- prestigious surface-mounted luminaire with round design and direct-indirect lighting for a balanced room ambience
- no UV and thermal emissions
- light component: direct 67% / indirect 33%
- sheet steel housing with removable LED unit
- opal insert pane made from acrylic glass
- easy screw mounting via ceiling bracket
- 5-pole terminal block
- ballast (LED converter) integrated (with DALI dimming)

Notes

Direct and indirect light component with separate dimming and switching available on request.

Standard options

4000 K

Special options



Lighting data / Norms

Lamps	LED Modul / CRI 80 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	25.5 W
Luminaire luminous flux	2890 lm
System efficiency	113.33 lm/W
UGR class	≤22
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Outer diameter	385 mm
Height	187 mm
Net weight	4.74 kg
Gross weight	5.33 kg

PLL 26.0385.830.1/DALI

PLL 26.0385.830.1/DALI

PL 26 (1xLED 26W 830/3000K 2890lm)



	C0	C90	C180	C270
0°	243	243	243	243
30°	201	201	201	201
60°	103	103	103	103
90°	1	1	1	1
120°	49	50	49	50
150°	101	102	101	102
180°	120	120	120	120
cd / 1000 lm				

LDC unsuitable for cone representation.
The C0 angle is oversized.

η	LED
Efficiency	111 lm/W
Direct/Indirect	↓ 67% / ↑ 33%
System Power	26 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.8
UGR C90/C270	19.8
CIE Flux Codes	48 79 96 67 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOR
Organic Response sensor for surface mounting