




PLL-ECO 593.0625.830.1




Colours	Article no.	EAN
	657743	4043544666482



Description

- light field for suspended ceiling systems with visible T profile module (625 x 625)
- homogeneous lighting surface
- low glare values
- no UV and thermal emissions
- outstanding ease of maintenance
- luminaire housing made from aluminium
- positioning of the ballast outside on the luminaire body is possible
- opal acrylic glass
- tool-free insertion into ceiling
- connection to ballast via luminaire cable with integrated plug
- ballast (LED converter) included

Standard options



Special options



Lighting data / Norms

Lamps	LED Modul / CRI 80 / 3000 K
EPREL light sources	832761
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	32.0 W
Luminaire luminous flux	3990 lm
System efficiency	124.68 lm/W
Module efficiency	189.48 lm/W
UGR class	≤22
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Length	619 mm
Width	619 mm
Height	65 mm
Recessed depth	100 mm
Net weight	4.16 kg
Gross weight	4.38 kg

PLL-ECO 593.0625.830.1

PLL-ECO 593.0625.830.1

PL 59 Eco (1xLED 32W 830/3000K 3990lm)



	C0	C90	C180	C270
0°	352	352	352	352
15°	338	338	338	338
30°	297	297	297	297
45°	233	235	233	235
60°	155	156	155	156
75°	65	66	65	66
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	8.96	9.03	156.0
6.0	17.93	18.07	39.0
9.0	26.89	27.10	17.3
12.0	35.85	36.14	9.7
15.0	44.82	45.17	6.2

η	LED
Efficiency	125 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	32 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.7
UGR C90/C270	20.7
CIE Flux Codes	47 79 96 100 100
Ra/CRI	>80

LTS