


# SCEKLP 6.2040.15



Colours	Article no.	EAN
black	637048	4043544396587
silver	637049	4043544396594
white	637050	4043544396600



## Description

- flexible recessed spotlight system consisting of recessed frames, light-heads and ballasts (recessed frames to be ordered separately)
- light-head pivots through 28° via gimbals
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management with passive cooling (heat sink made from aluminium)
- gimbals made from die-cast zinc and polycarbonate
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- clear safety glass
- light-head snaps into mounting frame without tools
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter) included (external placement)

## Standard options



## Special options



## Lighting data / Norms

Lamps	LED Spot / CRI 80 / 4000 K
EPREL light sources	848119
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	25.8 W
Luminaire luminous flux	2850 lm
System efficiency	110.46 lm/W
Module efficiency	160.37 lm/W
UGR class	≤19
Beam range	Spot
Beam angle	14°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	III
Type of protection	IP20

## Dimensions / Weights


Height	126 mm
Recessed depth	123 mm
Diameter of light head	154 mm
Net weight	0.80 kg
Gross weight	0.84 kg

# SCEKLP 6.2040.15

## SCEKLP 6.2040.15

Scene 6 System | Light-Head (1xLED 26W 840/4000K 2850lm)

— C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	6451	6451	6451	6451
15°	838	838	838	838
30°	372	372	372	372
45°	19	19	19	19
60°	1	1	1	1
75°	0	0	0	0
90°	0	0	0	0
cd / 1000 lm				


Offset [m] Cone width [m] Illuminance [lx]

C0-C180 Plane		
3.0	0.77	2042.7
6.0	1.54	510.7
9.0	2.30	227.0
12.0	3.07	127.7
15.0	3.84	81.7

<b>η</b>	LED
Efficiency	110 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	26 W
<b>UGR</b>	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	19.2
UGR C90/C270	19.2
CIE Flux Codes	98 100 100 100 100
Ra/CRI	>80

LTS


## Accessories




**SCER 6.100**  
mounting frame 1-lamp



**SCER 6.111**  
mounting frame (round) 1-lamp




**SCER 6.200**  
mounting frame 2-lamp




**SCER 6.300**  
mounting frame 3-lamp



**SCER 6.310**  
mounting frame (round) 3-lamp



**SCER 6.330**  
corner mounting frame 3-lamp



**SCER 6.400**  
mounting frame 4-lamp