


SCEKLP 6.3030.45



Colours	Article no.	EAN	
white	631220	4043544406644	
silver	631269	4043544406637	
black	631286	4043544406620	

















Description

- flexible recessed spotlight system consisting of recessed frames, light-heads and ballasts (recessed frames to be ordered separately)
- light-head pivots through 28° via gimbals
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management with passive cooling (heat sink made from aluminium)
- gimbals made from die-cast zinc and polycarbonate
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- · clear safety glass
- light-head snaps into mounting frame without tools
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter) included (external placement)

Standard options















Special options

















Lighting data / Norms

LED Spot / CRI 80 / 3000 K

EPREL light sources 851239 L90 B50 50.000 h

Lifetime L80 B50 100.000 h
L80 B20 50.000 h

 System power
 32.8 W

 Luminaire luminous flux
 3530 lm

 System efficiency
 107.62 lm/W

 Module efficiency
 158.91 lm/W

 UGR class
 ≤22

 Beam range
 Wide Flood

 Beam angle
 49°

Supply voltage 220 - 240 V / 50 - 60 Hz

Protection class III

Type of protection IP20

Dimensions / Weights


Height143 mmRecessed depth140 mmDiameter of light head154 mmNet weight0.94 kgGross weight0.99 kg

LTS LOVE TO SHINE


SCEKLP 6.3030.45

SCEKLP 6.3030.45

Scene 6 System | Light-Head (1xLED 33W 830/3000K 3530lm)



	C0	C90	C180	C270
0°	1418	1418	1418	1418
15°	1233	1233	1233	1233
30°	484	484	484	484
45°	16	16	16	16
60°	2	2	2	2
75°	1	1	1	1
90°	0	0	0	0



η	LED		
Efficiency	107 lm/W		
Direct/Indirect	↓ 100% / ↑ 0% 33 W		
System Power			
UGR	X=4H, Y=8H		
Reflection factors	70/50/20		
UGR C0/C180	20.9		
UGR C90/C270	20.9		
CIE Flux Codes	98 100 100 100 100		
Ra/CRI	>80		

LTS

Accessories



SCER 6.100 mounting frame 1-lamp



SCER 6.111 mounting frame (round) 1-lamp



SCER 6.200 mounting frame 2-lamp



SCER 6.300 mounting frame 3-lamp



SCER 6.310 mounting frame (round) 3-lamp



SCER 6.330 corner mounting frame 3-lamp



SCER 6.400 mounting frame 4-lamp