




SCELP 401.1030.45



Colours	Article no.	EAN
white	632166	4043544408051
silver	632167	4043544408068
black	632168	4043544408075



Description

- recessed spotlight with wide range of applications
- light-head pivots through 27° on gimbals
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management with passive cooling (heat sink made from aluminium)
- gimbals made from die-cast zinc
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- recessed ring made from sheet steel
- clear safety glass
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter) included (external placement)

Standard options



Special options



Lighting data / Norms

Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	848117
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	13.4 W
Luminaire luminous flux	1380 lm
System efficiency	102.98 lm/W
Module efficiency	156.64 lm/W
UGR class	≤19
Beam range	Wide Flood
Beam angle	49°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	II
Type of protection	IP20


Dimensions / Weights

Outer diameter	179 mm
Height	127 mm
Cut-out (Ø)	165 mm
Ceiling thickness	10.0 - 30.0 mm
Recessed depth	123 mm
Diameter of light head	140 mm
Net weight	1.05 kg

Recessed Spotlights · Scene 4

SCELP 401.1030.45

Gross weight



LTS
LOVE TO SHINE


1.10 kg

SCELP 401.1030.45

SCELP 401.1030.45


Scene 4 (1xLED 13W 830/3000K 1380lm 45°)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	1375	1375	1375	1375
15°	1215	1215	1215	1215
30°	498	498	498	498
45°	21	21	21	21
60°	1	1	1	1
75°	0	0	0	0
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]



η	LED
Efficiency	106 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	13 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	17.8
UGR C90/C270	17.8
CIE Flux Codes	98 100 100 100 100
Ra/CRI	>80

LTS

Accessories



ZBW20
honeycomb louvre