

Recessed Spotlights · Scene 4


# SCELP 401.20.35/F



| Colours | Article no. | EAN |
|---|---|---|
| black | 640095 | 4043544439390 |
| silver | 640096 | 4043544439406 |
| white | 640097 | 4043544439413 |




## Description

- recessed spotlight for special lighting of meat and sausage products
- light-head pivots through 27° on gimbals
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management with passive cooling (heat sink made from aluminium)
- gimbals made from die-cast zinc
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- recessed ring made from sheet steel
- clear safety glass
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter) included (external placement)

## Standard options

2700 K | 3000 K | 4000 K | BAKERY | DALI | 15° | 25° | 45°

## Special options

PRODUCE | BETON EINBAU | BLATTFEDER

## Lighting data / Norms

| | |
|---|---|
| Lamps | LED Spot Meat |
| Lifetime | L90 B50 50.000 h<br>L80 B50 100.000 h<br>L80 B20 50.000 h |
| System power | 40.0 W |
| Luminaire luminous flux | 2100 lm |
| System efficiency | 52.50 lm/W |
| Module efficiency | 76.00 lm/W |
| UGR class | ≤19 |
| Beam angle | 35° |
| Supply voltage | 220 - 240 V / 50 - 60 Hz |
| Protection class | III |
| Type of protection | IP20 |

## Dimensions / Weights


| | |
|---|---|
| Outer diameter | 179 mm |
| Height | 166 mm |
| Cut-out (Ø) | 165 mm |
| Ceiling thickness | 10.0 - 30.0 mm |
| Recessed depth | 162 mm |
| Diameter of light head | 140 mm |
| Net weight | 1.20 kg |
| Gross weight | 1.26 kg |

© LTS Licht & Leuchten GmbH · lts-light.com · Technical data are subject to change. · Version: 28.03.2024

# SCELP 401.20.35/F


**SCELP 401.20.35/F**

Scene 4 (1xLED 40W MEAT 2100lm 35°)




| | C0 | C90 | C180 | C270 |
|---|---|---|---|---|
| 0° | 2131 | 2131 | 2131 | 2131 |
| 15° | 1302 | 1302 | 1302 | 1302 |
| 30° | 395 | 395 | 395 | 395 |
| 45° | 25 | 25 | 25 | 25 |
| 60° | 3 | 3 | 3 | 3 |
| 75° | 0 | 0 | 0 | 0 |
| 90° | 0 | 0 | 0 | 0 |

cd / 1000 lm




| | |
|---|---|
| **η** | LED |
| Efficiency | 53 lm/W |
| Direct/Indirect | ↓ 100% / ↑ 0% |
| System Power | 40 W |
| **UGR** | X=4H, Y=8H |
| Reflection factors | 70/50/20 |
| UGR C0/C180 | 18.6 |
| UGR C90/C270 | 18.6 |
| CIE Flux Codes | 97 100 100 100 100 |
| Ra/CRI | --- |

LTS

## Accessories



**ZBW 20**
honeycomb louvre