




SCOUT 202.927.25.2/DALI-EU



Colours	Article no.	EAN
black	660376	4043544691958
silver	660377	4043544691965
white	660378	4043544691972



Description

- flexible track-mounted spotlight in separated design with cylindrical light-head
- light-head rotates through 355° and pivots through 90° via integrated articulated arm
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from die-cast aluminium
- innovative thermal management with design-integrated passive cooling
- high performance specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- ballast housing made from aluminium
- clear and reflection-free EnergyVision safety glass
- 3-phase track adapter DALI (Eutrac)
- ballast (LED converter DALI, dimmable) integrated

Standard options



Special options



Lighting data / Norms


Lamps	LED Spot / CRI 90 / 2700 K
EPREL light sources	857619
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	21.0 W
Luminaire luminous flux	2260 lm
System efficiency	107.61 lm/W
Module efficiency	132.86 lm/W
UGR class	≤16
Beam range	Medium Flood
Beam angle	26°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights

Length	178 mm
Width	96 mm
Height	185 mm
Diameter of light head	96 mm
Net weight	1.30 kg
Gross weight	1.37 kg

SCOUT 202.927.25.2/DALI-EU

Scout Next (1xLED 21W 927/2700K 2260lm 25°)



Offset [m]	Cone width [m]	Illuminance [lx]
3.0	1.37	858.4
6.0	2.74	214.6
9.0	4.11	95.4
12.0	5.48	53.6
15.0	6.84	34.3

C0-C180 Plane

η	LED
Efficiency	108 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	21 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	16.4
UGR C90/C270	16.4
CIE Flux Codes	99 100 100 100 100
Ra/CRI	>90

LTS

Accessories



ZBK 13
anti-glare flaps



ZBW 87
honeycomb louvre