




SCOUT 203.927.35.2/DALI-EU



Colours	Article no.	EAN
silver	660448	4043544692672
black	660449	4043544692689
white	660450	4043544692696



Description

- flexible track-mounted spotlight in separated design with cylindrical light-head
- light-head rotates through 355° and pivots through 90° via integrated articulated arm
- outstanding ease of maintenance
- no UV and thermal emissions
- light-head made from die-cast aluminium
- innovative thermal management with design-integrated passive cooling
- high performance specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- ballast housing made from aluminium
- clear and reflection-free EnergyVision safety glass
- 3-phase track adapter DALI (Eutrac)
- ballast (LED converter DALI, dimmable) integrated

Standard options



Special options



Lighting data / Norms


Lamps	LED Spot / CRI 90 / 2700 K
EPREL light sources	857619
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	29.2 W
Luminaire luminous flux	2990 lm
System efficiency	102.39 lm/W
Module efficiency	132.86 lm/W
UGR class	≤19
Beam range	Flood
Beam angle	36°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights

Length	178 mm
Width	96 mm
Height	185 mm
Diameter of light head	96 mm
Net weight	1.25 kg
Gross weight	1.34 kg

SCOUT 203.927.35.2/DALI-EU

Scout Next (1xLED 29W 927/2700K 2990lm 35°)



Offset [m] Cone width [m] Illuminance [lx]

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	1.90	781.8
6.0	3.79	195.5
9.0	5.69	86.9
12.0	7.59	48.9
15.0	9.48	31.3

η

Efficiency LED 103 lm/W

Direct/Indirect ↓ 100% / ↑ 0%

System Power 29 W

UGR X=4H, Y=8H

Reflection factors 70/50/20

UGR C0/C180 18.0

UGR C90/C270 18.0

CIE Flux Codes 99 100 100 100 100

Ra/CRI >90

Accessories



ZBK 13
anti-glare flaps



ZBW 87
honeycomb louvre